

Luminaire

Code BH10405+BH16301
 Name A.39 SHARP D+IND 2368 HB 34 300K ND SIL + COVER 6X4 OPT. HB WHITE

Measurem.

Code FTS1900547-B
 Name A.39 SHARP D+IND 2368 HB 34 300K ND SIL + COVER 6X4 OPT. HB WHITE

Luminaire Flux	10777 lm	Luminaire Power	125.0 W	Efficacy	86.217 lm/W	Efficiency	100.00%
Source Flux	10777 lm	Maximum value	1103.74 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	888 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.032856 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.007949 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-11-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		10777 lm	


LED Flux=13945lm LED Power=107W Eff=77% EfcLed=130lm/W EfcLum=86lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h

C.I.E. 97 99 100 43 100
 F UTE --

D DIN 5040
 B NBN

C62
 BZ 1

2368mm x 40mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 57.06 %
 DLOR 42.94 %
 RN 57.06 %

