

Luminaire


Code BH10801+BH16304
 Name A.39 SHARP D+IND 2368 HB 54 300K ND BCO + COVER 6X4 OPT. HB BLACK

Measurerm.

Code FTS1900265-B
 Name A.39 SHARP D+IND 2368 HB 54 300K ND BCO + COVER 6X4 OPT. HB BLACK

Luminaire Flux	10828 lm	Luminaire Power	125.0 W	Efficacy	86.620 lm/W	Efficiency	100.00%
Source Flux	10828 lm	Maximum value	618.18 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	888 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.032856 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.007949 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-11-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		10828 lm	
LED Flux=13945lm LED Power=107W Eff=78% EfcLed=130lm/W EfcLum=87lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h							
C.I.E.	99 100 100 43 100			D DIN 5040		C62	
F UTE	--			B NBN		BZ 1	

2368mm x 40mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 56.80 %

DLOR 43.20 %

RN 56.80 %

