

Luminaire

Code BH12404+BH16001
 Name A.39 SHARP D+IND 1184 LB 34 300K ND NRO + COVER 2X4 OPT. LB WHITE

Measurement

Code FTS1900331-A
 Name A.39 SHARP D+IND 1184 LB 34 300K ND NRO + COVER 2X4 OPT. LB WHITE

| | | | | | | | |
|--|------------------|-------------------------|---------------|-----------------------------|---------------|-------------------------|--------------------|
| Luminaire Flux | 4617 lm | Luminaire Power | 53.0 W | Efficacy | 87.113 lm/W | Efficiency | 100.00% |
| Source Flux | 4617 lm | Maximum value | 858.73 cd/klm | Position | C=0.00 G=0.00 | CG | Double Symmetrical |
| Rectangular Luminaire | | Length | 1184 mm | Width | 40 mm | Height | 111 mm |
| Rectangular Luminous Area | | Length | 296 mm | Width | 37 mm | Height | 0 mm |
| Horizontal Luminous Area | | 0.010952 m ² | | Emitting area on Plane 180° | | 0.000000 m ² | |
| Emitting area on Plane 0° | | 0.000000 m ² | | Emitting area on Plane 270° | | 0.000000 m ² | |
| Emitting area on Plane 90° | | 0.000000 m ² | | Glare area at 76° | | 0.002650 m ² | |
| Coordinate system | | CG | | Symmetry Type | | Double Symmetrical | |
| Date | | 21-11-2023 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 4617 lm | |
| LED Flux=5884lm LED Power=42W Eff=78% EfcLed=140lm/W EfcLum=87lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h | | | | | | | |
| C.I.E. | 97 99 100 33 100 | | | D DIN 5040 | | D62 | |
| F UTE | -- | | | B NBN | | BZ 1 | |

1184mm x 40mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 66.59 %
 DLOR 33.41 %
 RN 66.59 %



