

## Luminaire

Code BH12604+BH16001  
 Name A.39 SHARP D+IND 1184 LB 34 300K DM NRO + COVER 2X4 OPT. LB WHITE

## Measurem.

Code FTS1900331-A  
 Name A.39 SHARP D+IND 1184 LB 34 300K DM NRO + COVER 2X4 OPT. LB WHITE

Luminaire Flux	4617 lm	Luminaire Power	53.0 W	Efficacy	87.113 lm/W	Efficiency	100.00%
Source Flux	4617 lm	Maximum value	858.73 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1184 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	296 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.010952 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.002650 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-11-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4617 lm	


LED Flux=5884lm LED Power=42W Eff=78% EfcLed=140lm/W EfcLum=87lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h

C.I.E. 97 99 100 33 100  
 F UTE --

D DIN 5040  
 B NBN

D62  
 BZ 1

1184mm x 40mm



Semipiani C

180.0 — 0.0  
 270.0 — 90.0

ULOR 66.59 %  
 DLOR 33.41 %  
 RN 66.59 %

