


Luminaire

Code BH13001+BH16004
 Name A.39 SHARP D+IND 1184 LB 54 300K DM BCO + COVER 2X4 OPT. LB BLACK

Measurement

Code FTS1900049-A
 Name A.39 SHARP D+IND 1184 LB 54 300K DM BCO + COVER 2X4 OPT. LB BLACK

Luminaire Flux	4634 lm	Luminaire Power	53.0 W	Efficacy	87.434 lm/W	Efficiency	100.00%
Source Flux	4634 lm	Maximum value	481.45 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1184 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	296 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.010952 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.002650 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-11-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4634 lm	
LED Flux=5884lm LED Power=42W Eff=79% EfcLed=140lm/W EfcLum=87lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h							
C.I.E.	99 100 100 34 100			D DIN 5040		D62	
F UTE	--			B NBN		BZ 1	



Luminaire

Code BH13001+BH16004
Name A.39 SHARP D+IND 1184 LB 54 300K DM BCO + COVER 2X4 OPT. LB BLACK

Measurement


Code FTS1900049-A
Name A.39 SHARP D+IND 1184 LB 54 300K DM BCO + COVER 2X4 OPT. LB BLACK

Luminaire Flux	4634 lm	Luminaire Power	53.0 W	Efficacy	87.434 lm/W	Efficiency	100.00%
Source Flux	4634 lm	Maximum value	481.45 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1184 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	296 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.010952 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.002650 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-11-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4634 lm	
LED Flux=5884lm LED Power=42W Eff=79% EfcLed=140lm/W EfcLum=87lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h							
C.I.E.	99	100	100	34	100	D DIN 5040	D62
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.49	0.98	1.47	1.96	2.44	OC	0.49	0.98	1.47	1.96	2.44
OB	0.49	0.98	1.47	1.96	2.44	OD	0.49	0.98	1.47	1.96	2.44

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	2231.04	2215.00	2022.44	1345.26	238.20	34.75	2.71	0.00	0.00	0.00
OB	2231.04	2215.00	2022.44	1345.26	238.20	34.75	2.71	0.00	0.00	0.00
OC	2231.04	2215.00	2022.44	1345.26	238.20	34.75	2.71	0.00	0.00	0.00
OD	2231.04	2215.00	2022.44	1345.26	238.20	34.75	2.71	0.00	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=26.1°+26.1°	G=0.0
1.00	0.98	2231	1347		
2.00	1.96	558	337		
3.00	2.93	248	150		
4.00	3.91	139	84		
5.00	4.89	89	54		

H[m]	D[m]	Max lux	Med lux	Beta=26.1°+26.1°	G=0.0
1.00	0.98	2231	1347		
2.00	1.96	558	337		
3.00	2.93	248	150		
4.00	3.91	139	84		
5.00	4.89	89	54		