

Luminaire


Code BH14205+BH16204
 Name A.39 SHARP D+IND 2368 LB 17 300K DM SIL + COVER 4X4 OPT. LB BLACK

Measurem.

Code FTS1900181-A
 Name A.39 SHARP D+IND 2368 LB 17 300K DM SIL + COVER 4X4 OPT. LB BLACK

Luminaire Flux	9394 lm	Luminaire Power	104.0 W	Efficacy	90.327 lm/W	Efficiency	100.00%
Source Flux	9394 lm	Maximum value	1935.41 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	592 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.021904 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.005299 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-11-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		9394 lm	
LED Flux=11769lm LED Power=85W Eff=80% EfcLed=138lm/W EfcLum=90lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h							
C.I.E.	100 100 100 35 100			D DIN 5040		D62	
F UTE	--			B NBN		BZ 1	


2368mm x 40mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 65.46 %
 DLOR 34.54 %
 RN 65.46 %



Luminaire

Code BH14205+BH16204
Name A.39 SHARP D+IND 2368 LB 17 300K DM SIL + COVER 4X4 OPT. LB BLACK

Measurem.

Code FTS1900181-A
Name A.39 SHARP D+IND 2368 LB 17 300K DM SIL + COVER 4X4 OPT. LB BLACK

Luminaire Flux	9394 lm	Luminaire Power	104.0 W	Efficacy	90.327 lm/W	Efficiency	100.00%
Source Flux	9394 lm	Maximum value	1935.41 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	592 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.021904 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.005299 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-11-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		9394 lm	


LED Flux=11769lm LED Power=85W Eff=80% EfcLed=138lm/W EfcLum=90lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h

C.I.E.	100 100 100 35 100	D DIN 5040	D62
F UTE	--	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.18	0.35	0.53	0.70	0.88	OC	0.18	0.35	0.53	0.70	0.88
OB	0.18	0.35	0.53	0.70	0.88	OD	0.18	0.35	0.53	0.70	0.88

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	18181.23	15460.16	4746.75	1269.74	75.18	15.90	2.00	0.00	0.00	0.00
OB	18181.23	15460.16	4746.75	1269.74	75.18	15.90	2.00	0.00	0.00	0.00
OC	18181.23	15460.16	4746.75	1269.74	75.18	15.90	2.00	0.00	0.00	0.00
OD	18181.23	15460.16	4746.75	1269.74	75.18	15.90	2.00	0.00	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=10.0°+10.0°	G=0.0
1.00	0.35	18181	11600		
2.00	0.70	4545	2900		
3.00	1.05	2020	1289		
4.00	1.40	1136	725		
5.00	1.75	727	464		

H[m]	D[m]	Max lux	Med lux	Beta=10.0°+10.0°	G=0.0
1.00	0.35	18181	11600		
2.00	0.70	4545	2900		
3.00	1.05	2020	1289		
4.00	1.40	1136	725		
5.00	1.75	727	464		