

## Luminaire

Code BH15001+BH16204  
 Name A.39 SHARP D+IND 2368 LB 54 300K DM BCO + COVER 4X4 OPT. LB BLACK

## Measurement

Code FTS1900193-A  
 Name A.39 SHARP D+IND 2368 LB 54 300K DM BCO + COVER 4X4 OPT. LB BLACK

Luminaire Flux	9268 lm	Luminaire Power	104.0 W	Efficacy	89.115 lm/W	Efficiency	100.00%
Source Flux	9268 lm	Maximum value	481.45 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	592 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.021904 m <sup>2</sup>		Emitting area on Plane 180°		0.000000 m <sup>2</sup>	
Emitting area on Plane 0°		0.000000 m <sup>2</sup>		Emitting area on Plane 270°		0.000000 m <sup>2</sup>	
Emitting area on Plane 90°		0.000000 m <sup>2</sup>		Glare area at 76°		0.005299 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		21-11-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		9268 lm	


LED Flux=11769lm LED Power=85W Eff=79% EfcLed=138lm/W EfcLum=89lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h

C.I.E. 99 100 100 34 100  
 F UTE --

D DIN 5040  
 B NBN

D62  
 BZ 1

2368mm x 40mm



Semipiani C

180.0 ——— 0.0  
 270.0 ——— 90.0

ULOR 66.35 %

DLOR 33.65 %

RN 66.35 %

