

## Luminaire

Code BH15104+BH16204  
 Name A.39 SHARP D+IND 2368 LB 54 400K DM NRO + COVER 4X4 OPT. LB BLACK

## Measurem.

Code FTS1900211  
 Name A.39 SHARP D+IND 2368 LB 54 400K DM NRO + COVER 4X4 OPT. LB BLACK


Luminaire Flux	9514.06 lm	Luminaire Power	104.00 W	Efficacy	91.48 lm/W	Efficiency	100.00%
Sources Flux	9514.06 lm	Maximum value	501.92 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	592 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.021904 m <sup>2</sup>		Emitting area on Plane 180°		0.000000 m <sup>2</sup>	
Emitting area on Plane 0°		0.000000 m <sup>2</sup>		Emitting area on Plane 270°		0.000000 m <sup>2</sup>	
Emitting area on Plane 90°		0.000000 m <sup>2</sup>		Glare area at 76°		0.005299 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		17-07-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		9514.06 lm	

LED Flux=11915,8lm LED Power=95W Eff=80% EfcLed=125lm/W EfcLum=91lm/W Ra=90 SDCM=2 L90(20K)=118000h

C.I.E. 99 100 100 35 100  
 F UTE --

D DIN 5040  
 B NBN  
 D62  
 BZ 1

2368mm x 40mm



Semipiani C

180.0 — 0.0  
 270.0 — 90.0

ULOR 64.92 %

DLOR 35.08 %

RN 64.92 %

