

## Luminaire

Code BH23205+BH16301  
 Name A.39 RCS TRIM SHARP 2368 HB F 930 SLV + 6X4 OPT. HB WHITE

## Measurement

Code FTS1900749  
 Name A.39 RCS TRIM SHARP 2368 HB F 930 SLV + 6X4 OPT. HB WHITE


Luminaire Flux	4627.18 lm	Luminaire Power	66.00 W	Efficacy	70.11 lm/W	Efficiency	100.00%
Sources Flux	4627.18 lm	Maximum value	2570.73 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	888 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.032856 m <sup>2</sup>		Emitting area on Plane 180°		0.000000 m <sup>2</sup>	
Emitting area on Plane 0°		0.000000 m <sup>2</sup>		Emitting area on Plane 270°		0.000000 m <sup>2</sup>	
Emitting area on Plane 90°		0.000000 m <sup>2</sup>		Glare area at 76°		0.007949 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		16-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4627.18 lm	

LED Flux=6529,09lm LED Power=66W Eff=71% EfcLed=99lm/W EfcLum=70lm/W Ra=90 SDCM=2 L90(20K)=118000h

C.I.E. 97 99 100 100 100  
 F UTE --

D DIN 5040  
 B NBN  
 A60  
 BZ 1


2368mm x 40mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %  
 DLOR 100.00 %  
 RN 0.00 %



## Luminaire

Code BH23205+BH16301  
Name A.39 RCS TRIM SHARP 2368 HB F 930 SLV + 6X4 OPT. HB WHITE

## Measurerm.


Code FTS1900749  
Name A.39 RCS TRIM SHARP 2368 HB F 930 SLV + 6X4 OPT. HB WHITE

Luminaire Flux	4627.18 lm	Luminaire Power	66.00 W	Efficacy	70.11 lm/W	Efficiency	100.00%
Sources Flux	4627.18 lm	Maximum value	2570.73 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	888 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.032856 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.007949 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		16-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4627.18 lm	
LED Flux=6529,09lm LED Power=66W Eff=71% EfcLed=99lm/W EfcLum=70lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	97 99 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

### Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.33	0.66	0.98	1.31	1.64	OC	0.33	0.66	0.98	1.31	1.64
OB	0.33	0.66	0.98	1.31	1.64	OD	0.33	0.66	0.98	1.31	1.64

	Luminous Intensities [ cd/klm ]									
	0	5	15	25	35	45	55	65	75	85
OA	11895.25	11064.79	7318.68	2632.11	464.46	109.56	28.43	15.36	9.93	3.89
OB	11895.25	11064.79	7318.68	2632.11	464.46	109.56	28.43	15.36	9.93	3.89
OC	11895.25	11064.79	7318.68	2632.11	464.46	109.56	28.43	15.36	9.93	3.89
OD	11895.25	11064.79	7318.68	2632.11	464.46	109.56	28.43	15.36	9.93	3.89



H[m]	D[m]	Max lux	Med lux	Alpha=18.1°+18.1°	G=0.0
1.00	0.66	11895	6910		
2.00	1.31	2974	1727		
3.00	1.97	1322	768		
4.00	2.62	743	432		
5.00	3.28	476	276		