

Luminaire

Code BH26401+BH16201
 Name A.39 RCS TLESS SHARP 2368 LB XF 930 + 4X4 OPT. LB WHITE

Measurement

Code FTS1900729
 Name A.39 RCS TLESS SHARP 2368 LB XF 930 + 4X4 OPT. LB WHITE

Luminaire Flux	3194.53 lm	Luminaire Power	44.00 W	Efficacy	72.60 lm/W	Efficiency	100.00%
Sources Flux	3194.53 lm	Maximum value	1406.35 cd/klm	Position	C=0.00 G=1.00	CG	Rotosymmetrical
Rectangular Luminaire	Length	2368 mm	Width	40 mm	Height	111 mm	
Rectangular Luminous Area	Length	592 mm	Width	37 mm	Height	0 mm	
Horizontal Luminous Area	0.021904 m ²	Emitting area on Plane 180°	0.000000 m ²	Emitting area on Plane 270°	0.000000 m ²	Emitting area on Plane 90°	0.005299 m ²
Coordinate system	CG	Symmetry Type	Rotosymmetrical		Maximum Gamma Angle	180	
Date	17-07-2017	Measurement Flux	3194.53 lm				
Measurement Distance	0.00						


LED Flux=4352,8lm LED Power=44W Eff=73% EfcLed=99lm/W EfcLum=73lm/W Ra=90 SDCM=2 L90(20K)=118000h

C.I.E. 97 99 100 100 100
 F UTE --

D DIN 5040
 B NBN

A60
 BZ 1


2368mm x 40mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
 DLOR 100.00 %
 RN 0.00 %



Luminaire

Code BH26401+BH16201
Name A.39 RCS TLESS SHARP 2368 LB XF 930 + 4X4 OPT. LB WHITE

Measurerm.


Code FTS1900729
Name A.39 RCS TLESS SHARP 2368 LB XF 930 + 4X4 OPT. LB WHITE

Luminaire Flux	3194.53 lm	Luminaire Power	44.00 W	Efficacy	72.60 lm/W	Efficiency	100.00%
Sources Flux	3194.53 lm	Maximum value	1406.35 cd/klm	Position	C=0.00 G=1.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	592 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.021904 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.005299 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		17-07-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3194.53 lm	
LED Flux=4352,8lm LED Power=44W Eff=73% EfcLed=99lm/W EfcLum=73lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	97 99 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.49	0.98	1.47	1.96	2.45	OC	0.49	0.98	1.47	1.96	2.45
OB	0.49	0.98	1.47	1.96	2.45	OD	0.49	0.98	1.47	1.96	2.45

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	4492.61	4460.55	4060.31	2702.96	495.31	86.10	20.17	12.89	8.46	3.16
OB	4492.61	4460.55	4060.31	2702.96	495.31	86.10	20.17	12.89	8.46	3.16
OC	4492.61	4460.55	4060.31	2702.96	495.31	86.10	20.17	12.89	8.46	3.16
OD	4492.61	4460.55	4060.31	2702.96	495.31	86.10	20.17	12.89	8.46	3.16



H[m]	D[m]	Max lux	Med lux	Alpha=26.1°+26.1°	G=0.0 Max non a G
1.00	0.98	4493	2704		
2.00	1.96	1123	676		
3.00	2.94	499	300		
4.00	3.91	281	169		
5.00	4.89	180	108		