

Luminaire

Code BQ81301+AP91300
Name VECTOR 40 WALL SWITCH 927 WF WHT + SOFT FILTER

Measurement

Code FTS2300036
Name VECTOR 40 WALL SWITCH 927 WF WHT + SOFT FILTER

Luminaire Flux	306 lm	Luminaire Power	8.5 W	Efficacy	35.981 lm/W	Efficiency	100.00%
Source Flux	306 lm	Maximum value	3008.02 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	40 mm	Height	103 mm		
Round Luminous Area		Diam.	27 mm	Height	0 mm		
Horizontal Luminous Area			0.000573 m2	Emitting area on Plane 180°			0.000000 m2
Emitting area on Plane 0°			0.000000 m2	Emitting area on Plane 270°			0.000000 m2
Emitting area on Plane 90°			0.000000 m2	Glare area at 76°			0.000139 m2
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		08-11-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		306 lm	
LED Flux=660lm LED Power=6W Eff=46% EfcLed=107lm/W EfcLum=36lm/W CCT=2700K Ra=90 R9=50 SDCM=2 L70(6K)=50000h							
C.I.E.	96 99 100 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		


Diam=40mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
DLOR 100.00 %
RN 0.00 %



Luminaire

Code BQ81301+AP91300
Name VECTOR 40 WALL SWITCH 927 WF WHT + SOFT FILTER

Measurerm.

Code FTS2300036
Name VECTOR 40 WALL SWITCH 927 WF WHT + SOFT FILTER

Luminaire Flux	306 lm	Luminaire Power	8.5 W	Efficacy	35.981 lm/W	Efficiency	100.00%
Source Flux	306 lm	Maximum value	3008.02 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	40 mm	Height	103 mm		
Round Luminous Area		Diam.	27 mm	Height	0 mm		
Horizontal Luminous Area		0.000573 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.000139 m ²	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		08-11-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		306 lm	


LED Flux=660lm LED Power=6W Eff=46% EfcLed=107lm/W EfcLum=36lm/W CCT=2700K Ra=90 R9=50 SDCM=2 L70(6K)=50000h

C.I.E.	96 99 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.26	0.52	0.78	1.04	1.31	OC	0.26	0.52	0.78	1.04	1.31
OB	0.26	0.52	0.78	1.04	1.31	OD	0.26	0.52	0.78	1.04	1.31

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	919.97	845.43	444.72	146.77	39.86	10.67	3.16	1.35	0.59	0.07
OB	919.97	845.43	444.72	146.77	39.86	10.67	3.16	1.35	0.59	0.07
OC	919.97	845.43	444.72	146.77	39.86	10.67	3.16	1.35	0.59	0.07
OD	919.97	845.43	444.72	146.77	39.86	10.67	3.16	1.35	0.59	0.07



H[m]	D[m]	Max lux	Med lux	Alpha=14.6°+14.6°	G=0.0
1.00	0.52	920	563		
2.00	1.04	230	141		
3.00	1.57	102	63		
4.00	2.09	57	35		
5.00	2.61	37	23		