

## Luminaire

Code BQ91201+AP91300  
Name VECTOR 40 WALL NO SW 927 FL WHT + SOFT FILTER

## Measurem.

Code FTS2300033  
Name VECTOR 40 WALL NO SW 927 FL WHT + SOFT FILTER

Luminaire Flux	312 lm	Luminaire Power	8.5 W	Efficacy	36.751 lm/W	Efficiency	100.00%
Source Flux	312 lm	Maximum value	3823.34 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	40 mm	Height	103 mm		
Round Luminous Area		Diam.	27 mm	Height	0 mm		
Horizontal Luminous Area			0.000573 m2	Emitting area on Plane 180°			0.000000 m2
Emitting area on Plane 0°			0.000000 m2	Emitting area on Plane 270°			0.000000 m2
Emitting area on Plane 90°			0.000000 m2	Glare area at 76°			0.000139 m2
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		08-11-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		312 lm	
LED Flux=660lm LED Power=6W Eff=47% EfcLed=107lm/W EfcLum=37lm/W CCT=2700K Ra=90 R9=50 SDCM=2 L70(6K)=50000h							
C.I.E.	97 99 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

Diam=40mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



## Luminaire

Code BQ91201+AP91300  
Name VECTOR 40 WALL NO SW 927 FL WHT + SOFT FILTER

## Measur.


Code FTS2300033  
Name VECTOR 40 WALL NO SW 927 FL WHT + SOFT FILTER

Luminaire Flux	312 lm	Luminaire Power	8.5 W	Efficacy	36.751 lm/W	Efficiency	100.00%
Source Flux	312 lm	Maximum value	3823.34 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	40 mm	Height	103 mm		
Round Luminous Area		Diam.	27 mm	Height	0 mm		
Horizontal Luminous Area		0.000573 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000139 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		08-11-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		312 lm	
LED Flux=660lm LED Power=6W Eff=47% EfcLed=107lm/W EfcLum=37lm/W CCT=2700K Ra=90 R9=50 SDCM=2 L70(6K)=50000h							
C.I.E.	97 99 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

### Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.23	0.45	0.68	0.91	1.14	OC	0.23	0.45	0.68	0.91	1.14
OB	0.23	0.45	0.68	0.91	1.14	OD	0.23	0.45	0.68	0.91	1.14

	Luminous Intensities [ cd/klm ]									
	0	5	15	25	35	45	55	65	75	85
OA	1194.34	1069.41	471.10	128.02	28.25	6.66	2.20	1.21	0.61	0.16
OB	1194.34	1069.41	471.10	128.02	28.25	6.66	2.20	1.21	0.61	0.16
OC	1194.34	1069.41	471.10	128.02	28.25	6.66	2.20	1.21	0.61	0.16
OD	1194.34	1069.41	471.10	128.02	28.25	6.66	2.20	1.21	0.61	0.16



H[m]	D[m]	Max lux	Med lux	Alpha=12.8°+12.8°	G=0.0
1.00	0.45	1194	741		
2.00	0.91	299	185		
3.00	1.36	133	82		
4.00	1.82	75	46		
5.00	2.27	48	30		