


Luminaire

Code BZ01701+BZ06101
 Name A.39 S/C SHARP REFR.DIR 2368 840 ND BCO + KIT LOUVRES 2368 BCO

Measurement

Code FTS2102145-A
 Name A.39 S/C SHARP REFR.DIR 2368 840 ND BCO + KIT LOUVRES 2368 BCO

Luminaire Flux	10621 lm	Luminaire Power	70.0 W	Efficacy	151.729 lm/W	Efficiency	100.00%
Source Flux	10621 lm	Maximum value	1075.90 cd/klm	Position	C=80.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	2363 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.082705 m ²		Emitting area on Plane 180°	0.000000 m ²		
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°	0.000000 m ²		
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°	0.020008 m ²		
Coordinate system		CG		Symmetry Type	Double Symmetrical		
Date		08-11-2023		Maximum Gamma Angle	180		
Measurement Distance		0.00		Measurement Flux	10621 lm		
LED Flux=11734lm LED Power=62W Eff=91% EfcLed=188lm/W EfcLum=152lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(6K)=50000h							
C.I.E.	93 97 99 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		



Luminaire

Code BZ01701+BZ06101
 Name A.39 S/C SHARP REFR.DIR 2368 840 ND BCO + KIT LOUVRES 2368 BCO

Measurerm.


Code FTS2102145-A
 Name A.39 S/C SHARP REFR.DIR 2368 840 ND BCO + KIT LOUVRES 2368 BCO

Luminaire Flux	10621 lm	Luminaire Power	70.0 W	Efficacy	151.729 lm/W	Efficiency	100.00%
Source Flux	10621 lm	Maximum value	1075.90 cd/klm	Position	C=80.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	2363 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.082705 m2		Emitting area on Plane 180°	0.000000 m2		
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°	0.000000 m2		
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°	0.020008 m2		
Coordinate system		CG		Symmetry Type	Double Symmetrical		
Date		08-11-2023		Maximum Gamma Angle	180		
Measurement Distance		0.00		Measurement Flux	10621 lm		
LED Flux=11734lm LED Power=62W Eff=91% EfcLed=188lm/W EfcLum=152lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(6K)=50000h							
C.I.E.	93 97 99 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.59	1.18	1.78	2.37	2.96	OC	0.59	1.19	1.78	2.37	2.97
OB	0.59	1.18	1.78	2.37	2.96	OD	0.59	1.19	1.78	2.37	2.97

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	11424.39	11273.60	10178.87	8124.44	2694.22	317.64	208.60	153.73	91.32	28.23
OB	11424.39	11273.60	10178.87	8124.44	2694.22	317.64	208.60	153.73	91.32	28.23
OC	11424.39	11310.19	10216.49	8125.82	2966.07	318.44	208.15	152.86	90.17	28.52
OD	11424.39	11310.19	10216.49	8125.82	2966.07	318.44	208.15	152.86	90.17	28.52



H[m]	D[m]	Max lux	Med lux	Alpha=30.6°+30.6°	G=0.0
1.00	1.18	11424	6028		
2.00	2.37	2856	1507		
3.00	3.55	1269	670		
4.00	4.74	714	377		
5.00	5.92	457	241		

H[m]	D[m]	Max lux	Med lux	Beta=30.7°+30.7°	G=0.0
1.00	1.19	11424	6028		
2.00	2.37	2856	1507		
3.00	3.56	1269	670		
4.00	4.75	714	377		
5.00	5.94	457	241		