

Luminaire

Code BZ02105IN0+BZ06201
 Name A.39 S/C SHARP REFR.DIR 2960 WIN ND SILA.39 S/C SHARP REFR KIT LOUVRES 2960 BCO

Measurement

Code FTS2103049
 Name A.39 S/C SHARP REFR.DIR 2960 WIN ND SILA.39 S/C SHARP REFR KIT LOUVRES 2960 BCO

Luminaire Flux	11582 lm	Luminaire Power	86.0 W	Efficacy	134.674 lm/W	Efficiency	100.00%
Source Flux	11582 lm	Maximum value	1168.42 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2960 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	2950 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.103250 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.024978 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		14-12-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		11582 lm	
LED Flux=12849lm LED Power=78W Eff=90% EfcLed=165lm/W EfcLum=135lm/W CCT=5000 Ra=90 SDCM=3 L70(9K)=50000h							
C.I.E.	98	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	



