

## Luminaire

Code BZ03105+BZ06204  
 Name A.39 S/C SHARP REFR.DIR 2960 830 DALISIL + KIT LOUVRES 2960 NRO

## Measurement

Code FTS2102067-A  
 Name A.39 S/C SHARP REFR.DIR 2960 830 DALISIL + KIT LOUVRES 2960 NRO

Luminaire Flux	11210 lm	Luminaire Power	86.0 W	Efficacy	130.349 lm/W	Efficiency	100.00%
Source Flux	11210 lm	Maximum value	1170.52 cd/klm	Position	C=5.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2960 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	2950 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.103250 m2		Emitting area on Plane 180°	0.000000 m2		
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°	0.000000 m2		
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°	0.024978 m2		
Coordinate system		CG		Symmetry Type	Double Symmetrical		
Date		02-11-2023		Maximum Gamma Angle	180		
Measurement Distance		0.00		Measurement Flux	11210 lm		


LED Flux=13932lm LED Power=78W Eff=80% EfcLed=179lm/W EfcLum=130lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(6K)=50000h

C.I.E. 98 100 100 100 100  
 F UTE --

D DIN 5040  
 B NBN

A60  
 BZ 1

2960mm x 45mm



Semipiani C

180.0 — 0.0  
 270.0 — 90.0

ULOR 0.00 %  
 DLOR 100.00 %  
 RN 0.00 %

