

Luminaire

Code BZ03805+BZ06001
 Name A.39 S SHARP REFR.D+I 1482 840 N/D SIL + KIT LOUVRES 1482 BCO

Measurement

Code FTS2102181-A
 Name A.39 S SHARP REFR.D+I 1482 840 N/D SIL + KIT LOUVRES 1482 BCO

Luminaire Flux	10298 lm	Luminaire Power	74.0 W	Efficacy	139.162 lm/W	Efficiency	100.00%
Source Flux	10298 lm	Maximum value	693.52 cd/klm	Position	C=80.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1480 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	1475 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.051625 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.012489 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		08-11-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		10298 lm	


LED Flux=11635lm LED Power=66W Eff=89% EfcLed=175lm/W EfcLum=139lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(6K)=50000h

C.I.E. 93 97 99 64 100
 F UTE 0.64 A + 0.36 T

D DIN 5040
 B NBN

B61
 BZ 1

1480mm x 45mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 35.54 %
 DLOR 64.46 %
 RN 35.54 %

