

Luminaire

Code BZ03905IN0+BZ06001
 Name A.39 S SHARP REFR.D+I 1482 WIN N/D SIL+ A.39 S/C SHARP REFR KIT LOUVRES 1482 BCO

Measurement

Code FTS2103073-A
 Name A.39 S SHARP REFR.D+I 1482 WIN N/D SIL+ A.39 S/C SHARP REFR KIT LOUVRES 1482 BCO

Luminaire Flux	8814 lm	Luminaire Power	74.0 W	Efficacy	119.109 lm/W	Efficiency	100.00%
Source Flux	8814 lm	Maximum value	767.67 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1480 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	1475 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.051625 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.012489 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		16-05-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		8814 lm	


LED Flux=9977lm LED Power=66W Eff=88% EfcLed=150lm/W EfcLum=119lm/W CCT=5000K Ra=90 SDCM=3 L70(9K)=50000h

C.I.E. 98 100 100 66 100
 F UTE --

D DIN 5040
 B NBN

B61
 BZ 1

1480mm x 45mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 34.30 %

DLOR 65.70 %

RN 34.30 %

