

Luminaire

Code BZ03905IN0+BZ06004
 Name A.39 S SHARP REFR.D+I 1482 WIN N/D SIL+ A.39 S/C SHARP REFR KIT LOUVRES 1482 NRO

Measurement

Code FTS2103079-A
 Name A.39 S SHARP REFR.D+I 1482 WIN N/D SIL+ A.39 S/C SHARP REFR KIT LOUVRES 1482 NRO

Luminaire Flux	8255 lm	Luminaire Power	74.0 W	Efficacy	111.552 lm/W	Efficiency	100.00%
Source Flux	8255 lm	Maximum value	740.52 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1480 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	1475 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.051625 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.012489 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		16-05-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		8255 lm	


LED Flux=9977lm LED Power=66W Eff=83% EfcLed=150lm/W EfcLum=112lm/W CCT=5000K Ra=90 SDCM=3 L70(9K)=50000h

C.I.E. 98 100 100 63 100
 F UTE --

D DIN 5040
 B NBN

B61
 BZ 1

1480mm x 45mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 36.62 %
 DLOR 63.38 %
 RN 36.62 %

