

## Luminaire

Code BZ04201IN0+BZ06104  
 Name A.39 S SHARP REFR.D+I 2368 WIN N/D BCO + A.39 S/C SHARP REFR KIT LOUVRES 2368 NRO

## Measurem.

Code FTS2103091-A  
 Name A.39 S SHARP REFR.D+I 2368 WIN N/D BCO + A.39 S/C SHARP REFR KIT LOUVRES 2368 NRO


Luminaire Flux	12905 lm	Luminaire Power	120.0 W	Efficacy	107.546 lm/W	Efficiency	100.00%
Source Flux	12905 lm	Maximum value	757.86 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	2363 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.082705 m <sup>2</sup>		Emitting area on Plane 180°		0.000000 m <sup>2</sup>	
Emitting area on Plane 0°		0.000000 m <sup>2</sup>		Emitting area on Plane 270°		0.000000 m <sup>2</sup>	
Emitting area on Plane 90°		0.000000 m <sup>2</sup>		Glare area at 76°		0.020008 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		16-05-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		12905 lm	

LED Flux=15607lm LED Power=104W Eff=83% EfcLed=151lm/W EfcLum=108lm/W CCT=5000K Ra=90 SDCM=3 L70(9K)=50000hLED Flux=15607lm LED Power=104W

C.I.E. 98 100 100 65 100  
 F UTE --

D DIN 5040 B61  
 B NBN BZ 1

2368mm x 45mm



Semipiani C

180.0 — 0.0  
 270.0 — 90.0

ULOR 35.14 %  
 DLOR 64.86 %  
 RN 35.14 %

