

Luminaire

Code BZ05405IN0+BZ06104
 Name A.39 S SHARP REFR.D+I 2368 WIN DALISIL + A.39 S/C SHARP REFR KIT LOUVRES 2368 NRO

Measurement

Code FTS2103091-A
 Name A.39 S SHARP REFR.D+I 2368 WIN DALISIL + A.39 S/C SHARP REFR KIT LOUVRES 2368 NRO

Luminaire Flux	12905 lm	Luminaire Power	120.0 W	Efficacy	107.546 lm/W	Efficiency	100.00%
Source Flux	12905 lm	Maximum value	757.86 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	2363 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.082705 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.020008 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		16-05-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		12905 lm	


LED Flux=15607lm LED Power=104W Eff=83% EfcLed=151lm/W EfcLum=108lm/W CCT=5000K Ra=90 SDCM=3 L70(9K)=50000hLED Flux=15607lm LED Power=104W

C.I.E. 98 100 100 65 100
 F UTE --

D DIN 5040
 B NBN

B61
 BZ 1

2368mm x 45mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 35.14 %
 DLOR 64.86 %
 RN 35.14 %

