

Luminaire

Code BZ05701IN0+BZ06201
 Name A.39 S SHARP REFR.D+I 2960 WIN DALIBCOA.39 S\C SHARP REFR KIT LOUVRES 2960 BCO

Measurement

Code FTS2103097-A
 Name A.39 S SHARP REFR.D+I 2960 WIN DALIBCOA.39 S\C SHARP REFR KIT LOUVRES 2960 BCO


Luminaire Flux	17628 lm	Luminaire Power	153.0 W	Efficacy	115.217 lm/W	Efficiency	100.00%
Source Flux	17628 lm	Maximum value	767.67 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2960 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	2950 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.103250 m2		Emitting area on Plane 180°	0.000000 m2		
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°	0.000000 m2		
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°	0.024978 m2		
Coordinate system		CG		Symmetry Type	Double Symmetrical		
Date		16-05-2022		Maximum Gamma Angle	180		
Measurement Distance		0.00		Measurement Flux	17628 lm		

LED Flux=19953lm LED Power=133W Eff=88% EfcLed=150lm/W EfcLum=115lm/W CCT=5000K Ra=90 SDCM=3 L70(9K)=50000h

C.I.E. 98 100 100 66 100
 F UTE --

D DIN 5040 B61
 B NBN BZ 1

2960mm x 45mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 34.30 %
 DLOR 65.70 %
 RN 34.30 %

