

Luminaire

Code CA12204+AP91400
 Name GOPLE 80 SPOT TRK16 48V WF 4000K NRO + VECTOR 55 - ANTI-DUZZLE LOUVRE

Measurement

Code FTS2200071
 Name GOPLE 80 SPOT TRK16 48V WF 4000K NRO + VECTOR 55 - ANTI-DUZZLE LOUVRE

| | | | | | | | |
|--|---------|-------------------------|----------------|-----------------------------|---------------|-------------------------|-----------------|
| Luminaire Flux | 1360 lm | Luminaire Power | 23.0 W | Efficacy | 59.137 lm/W | Efficiency | 100.00% |
| Source Flux | 1360 lm | Maximum value | 4326.59 cd/klm | Position | C=0.00 G=0.00 | CG | Rotosymmetrical |
| Round Luminaire | | Diam. | 77 mm | Height | 150 mm | | |
| Round Luminous Area | | Diam. | 46 mm | Height | 0 mm | | |
| Horizontal Luminous Area | | 0.001662 m ² | | Emitting area on Plane 180° | | 0.000000 m ² | |
| Emitting area on Plane 0° | | 0.000000 m ² | | Emitting area on Plane 270° | | 0.000000 m ² | |
| Emitting area on Plane 90° | | 0.000000 m ² | | Glare area at 76° | | 0.000402 m ² | |
| Coordinate system | | CG | | Symmetry Type | | Rotosymmetrical | |
| Date | | 01-03-2022 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 1360 lm | |
| LED Flux=2473lm LED Power=22W Eff=55% EfcLed=114lm/W EfcLum=59lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(6K)=50000h | | | | | | | |
| C.I.E. | 100 | 100 | 100 | 100 | D DIN 5040 | A60 | |
| F UTE | -- | | | | B NBN | BZ 1 | |

Diam=77mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR 100.00 %

RN 0.00 %



Luminaire

Code CA12204+AP91400
 Name GOPLE 80 SPOT TRK16 48V WF 4000K NRO + VECTOR 55 - ANTI-DUZZLE LOUVRE

Measurerm.


Code FTS2200071
 Name GOPLE 80 SPOT TRK16 48V WF 4000K NRO + VECTOR 55 - ANTI-DUZZLE LOUVRE

| | | | | | | | |
|--|---------|-----------------|----------------|-----------------------------|---------------|-----------------|-----------------|
| Luminaire Flux | 1360 lm | Luminaire Power | 23.0 W | Efficacy | 59.137 lm/W | Efficiency | 100.00% |
| Source Flux | 1360 lm | Maximum value | 4326.59 cd/klm | Position | C=0.00 G=0.00 | CG | Rotosymmetrical |
| Round Luminaire | | Diam. | 77 mm | Height | 150 mm | | |
| Round Luminous Area | | Diam. | 46 mm | Height | 0 mm | | |
| Horizontal Luminous Area | | 0.001662 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.000402 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Rotosymmetrical | |
| Date | | 01-03-2022 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 1360 lm | |
| LED Flux=2473lm LED Power=22W Eff=55% EfcLed=114lm/W EfcLum=59lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(6K)=50000h | | | | | | | |
| C.I.E. | 100 | 100 | 100 | 100 | 100 | D DIN 5040 | A60 |
| F UTE | -- | | | | | B NBN | BZ 1 |

Width at 50.00 % of Max Intensity

| H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 | H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 |
|------|------|------|------|------|------|------|------|------|------|------|------|
| OA | 0.25 | 0.50 | 0.76 | 1.01 | 1.26 | OC | 0.25 | 0.50 | 0.76 | 1.01 | 1.26 |
| OB | 0.25 | 0.50 | 0.76 | 1.01 | 1.26 | OD | 0.25 | 0.50 | 0.76 | 1.01 | 1.26 |

| | Luminous Intensities [cd/klm] | | | | | | | | | |
|----|---------------------------------|---------|---------|--------|-------|------|------|------|------|------|
| | 0 | 5 | 15 | 25 | 35 | 45 | 55 | 65 | 75 | 85 |
| OA | 5884.77 | 5399.49 | 2659.89 | 211.56 | 19.32 | 4.78 | 1.63 | 0.52 | 0.36 | 0.30 |
| OB | 5884.77 | 5399.49 | 2659.89 | 211.56 | 19.32 | 4.78 | 1.63 | 0.52 | 0.36 | 0.30 |
| OC | 5884.77 | 5399.49 | 2659.89 | 211.56 | 19.32 | 4.78 | 1.63 | 0.52 | 0.36 | 0.30 |
| OD | 5884.77 | 5399.49 | 2659.89 | 211.56 | 19.32 | 4.78 | 1.63 | 0.52 | 0.36 | 0.30 |



| H[m] | D[m] | Max lux | Med lux | Alpha=14.1°+14.1° | G=0.0 |
|------|------|---------|---------|-------------------|-------|
| 1.00 | 0.50 | 5885 | 3651 | | |
| 2.00 | 1.01 | 1471 | 913 | | |
| 3.00 | 1.51 | 654 | 406 | | |
| 4.00 | 2.01 | 368 | 228 | | |
| 5.00 | 2.52 | 235 | 146 | | |