

Luminaire

Code CA21104+AP90300
 Name GOPLE 60 S / TRK16 48V 3000K FL NRO + VECTOR 40 - SOFT FILTER

Measurement

Code FTS2200090
 Name GOPLE 60 S / TRK16 48V 3000K FL NRO + VECTOR 40 - SOFT FILTER

Luminaire Flux	410 lm	Luminaire Power	9.0 W	Efficacy	45.594 lm/W	Efficiency	100.00%
Source Flux	410 lm	Maximum value	3823.34 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	55 mm	Height	110 mm		
Round Luminous Area		Diam.	35 mm	Height	0 mm		
Horizontal Luminous Area			0.000962 m2	Emitting area on Plane 180°			0.000000 m2
Emitting area on Plane 0°			0.000000 m2	Emitting area on Plane 270°			0.000000 m2
Emitting area on Plane 90°			0.000000 m2	Glare area at 76°			0.000233 m2
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		07-03-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		410 lm	
LED Flux=867lm LED Power=7.9W Eff=47% EfcLed=110lm/W EfcLum=46lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(6K)=50000h							
C.I.E.	97 99 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		


Diam=55mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
 DLOR 100.00 %
 RN 0.00 %



Luminaire

Code CA21104+AP90300
 Name GOPLE 60 S / TRK16 48V 3000K FL NRO + VECTOR 40 - SOFT FILTER

Measurerm.


Code FTS2200090
 Name GOPLE 60 S / TRK16 48V 3000K FL NRO + VECTOR 40 - SOFT FILTER

Luminaire Flux	410 lm	Luminaire Power	9.0 W	Efficacy	45.594 lm/W	Efficiency	100.00%
Source Flux	410 lm	Maximum value	3823.34 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	55 mm	Height	110 mm		
Round Luminous Area		Diam.	35 mm	Height	0 mm		
Horizontal Luminous Area		0.000962 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000233 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		07-03-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		410 lm	
LED Flux=867lm LED Power=7.9W Eff=47% EfcLed=110lm/W EfcLum=46lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(6K)=50000h							
C.I.E.	97 99 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.23	0.45	0.68	0.91	1.14	OC	0.23	0.45	0.68	0.91	1.14
OB	0.23	0.45	0.68	0.91	1.14	OD	0.23	0.45	0.68	0.91	1.14

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1568.91	1404.81	618.84	168.17	37.11	8.74	2.89	1.59	0.80	0.21
OB	1568.91	1404.81	618.84	168.17	37.11	8.74	2.89	1.59	0.80	0.21
OC	1568.91	1404.81	618.84	168.17	37.11	8.74	2.89	1.59	0.80	0.21
OD	1568.91	1404.81	618.84	168.17	37.11	8.74	2.89	1.59	0.80	0.21



H[m]	D[m]	Max lux	Med lux	Alpha=12.8°+12.8°	G=0.0
1.00	0.45	1569	973		
2.00	0.91	392	243		
3.00	1.36	174	108		
4.00	1.82	98	61		
5.00	2.27	63	39		