

## Luminaire

Code CE13105+BZ07101  
 Name SHARP REFRACTIVE TRIM 4 UNIT 3000K WF SIL + SHARP REFRACTIVE KIT LOUVRES 1 UNIT BCO

## Measurement

Code FTS2200271  
 Name SHARP REFRACTIVE TRIM 4 UNIT 3000K WF SIL + SHARP REFRACTIVE KIT LOUVRES 1 UNIT BCO

|                            |         |                         |                |                             |               |                         |                    |
|----------------------------|---------|-------------------------|----------------|-----------------------------|---------------|-------------------------|--------------------|
| Luminaire Flux             | 1150 lm | Luminaire Power         | 8.0 W          | Efficacy                    | 143.710 lm/W  | Efficiency              | 100.00%            |
| Source Flux                | 1150 lm | Maximum value           | 1066.40 cd/klm | Position                    | C=0.00 G=0.00 | CG                      | Double Symmetrical |
| Rectangular Luminaire      |         | Length                  | 164 mm         | Width                       | 55 mm         | Height                  | 55 mm              |
| Rectangular Luminous Area  |         | Length                  | 140 mm         | Width                       | 35 mm         | Height                  | 0 mm               |
| Horizontal Luminous Area   |         | 0.004900 m <sup>2</sup> |                | Emitting area on Plane 180° |               | 0.000000 m <sup>2</sup> |                    |
| Emitting area on Plane 0°  |         | 0.000000 m <sup>2</sup> |                | Emitting area on Plane 270° |               | 0.000000 m <sup>2</sup> |                    |
| Emitting area on Plane 90° |         | 0.000000 m <sup>2</sup> |                | Glare area at 76°           |               | 0.001185 m <sup>2</sup> |                    |
| Coordinate system          |         | CG                      |                | Symmetry Type               |               | Double Symmetrical      |                    |
| Date                       |         | 04-10-2022              |                | Maximum Gamma Angle         |               | 180                     |                    |
| Measurement Distance       |         | 0.00                    |                | Measurement Flux            |               | 1150 lm                 |                    |


LED Flux=1270lm LED Power=8W Eff=91% EfcLed=159lm/W EfcLum=144lm/W CCT=3000K Ra=90 SDCM=3 L70(6K)=50000h

C.I.E. 92 97 99 100 100  
 F UTE 1.00 A

D DIN 5040  
 B NBN

A60  
 BZ 1

164mm x 55mm



Semipiani C

180.0 — 0.0  
 270.0 — 90.0

ULOR 0.00 %  
 DLOR 100.00 %  
 RN 0.00 %

