

Luminaire

Code CE13305+BZ07101
 Name SHARP REFRACTIVE TRIM 4 UNIT 4000K WF SIL + SHARP REFRACTIVE KIT LOUVRES 1 UNIT BCO

Measurement

Code FTS2200275-A
 Name SHARP REFRACTIVE TRIM 4 UNIT 4000K WF SIL + SHARP REFRACTIVE KIT LOUVRES 1 UNIT BCO

Luminaire Flux	1214 lm	Luminaire Power	8.0 W	Efficacy	151.750 lm/W	Efficiency	100.00%
Source Flux	1214 lm	Maximum value	1066.40 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	164 mm	Width	55 mm	Height	55 mm
Rectangular Luminous Area		Length	140 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.004900 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.001185 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		29-09-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1214 lm	


LED Flux=1341lm LED Power=8W Eff=91% EfcLed=168lm/W EfcLum=152lm/W CCT=4000K Ra=90 SDCM=3 L70(6K)=50000h

C.I.E. 92 97 99 100 100
 F UTE 1.00 A

D DIN 5040
 B NBN

A60
 BZ 1

164mm x 55mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 0.00 %
 DLOR 100.00 %
 RN 0.00 %

