

## Luminaire


Code CE13401IN0+BZ07101  
 Name SHARP REFRACTIVE TRIM 4 UNIT WI WF BCO + SHARP REFRACTIVE KIT LOUVRES 1 UNIT BCO

## Measurement

Code FTS2200279-A  
 Name SHARP REFRACTIVE TRIM 4 UNIT WI WF BCO + SHARP REFRACTIVE KIT LOUVRES 1 UNIT BCO

Luminaire Flux	1196 lm	Luminaire Power	8.0 W	Efficacy	149.485 lm/W	Efficiency	100.00%
Source Flux	1196 lm	Maximum value	1066.40 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire	Length	164 mm	Width	55 mm	Height	55 mm	55 mm
Rectangular Luminous Area	Length	140 mm	Width	35 mm	Height	0 mm	0 mm
Horizontal Luminous Area	0.004900 m <sup>2</sup>	Emitting area on Plane 180°		0.000000 m <sup>2</sup>	Emitting area on Plane 270°		0.001185 m <sup>2</sup>
Emitting area on Plane 0°	0.000000 m <sup>2</sup>	Emitting area on Plane 270°		0.000000 m <sup>2</sup>	Emitting area on Plane 180°		0.001185 m <sup>2</sup>
Emitting area on Plane 90°	0.000000 m <sup>2</sup>	Glare area at 76°		0.001185 m <sup>2</sup>			
Coordinate system	CG	Symmetry Type		Double Symmetrical			
Date	08-02-2023	Maximum Gamma Angle		180			
Measurement Distance	0.00	Measurement Flux		1196 lm			
LED Flux=1321lm LED Power=8W Eff=91% EfcLed=165lm/W EfcLum=149lm/W CCT=5000K Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	92 97 99 100 100	D DIN 5040		A60			
F UTE	1.00 A	B NBN		BZ 1			

164mm x 55mm



Semipiani C

180.0 — 0.0  
 270.0 — 90.0

ULOR 0.00 %  
 DLOR 100.00 %  
 RN 0.00 %

