

## Luminaire

Code CE15101+BZ07301  
 Name SHARP REFRACTIVE TRIM 12 UNIT 3000K WF BCO + SHARP REFRACTIVE KIT LOUVRES 3 UNIT BCO

## Measurement

Code FTS2200273  
 Name SHARP REFRACTIVE TRIM 12 UNIT 3000K WF BCO + SHARP REFRACTIVE KIT LOUVRES 3 UNIT BCO

Luminaire Flux	3449 lm	Luminaire Power	24.0 W	Efficacy	143.710 lm/W	Efficiency	100.00%
Source Flux	3449 lm	Maximum value	1066.40 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	460 mm	Width	55 mm	Height	55 mm
Rectangular Luminous Area		Length	420 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.014700 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.003556 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		04-10-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3449 lm	
LED Flux=3811lm LED Power=24W Eff=91% EfcLed=159lm/W EfcLum=144lm/W CCT=3000K Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	92 97 99 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		



