

## Luminaire

Code CE15104+BZ07304

Name SHARP REFRACTIVE TRIM 12 UNIT 3000K WF NRO + SHARP REFRACTIVE KIT LOUVRES 3 UNIT NRO

## Measurement

Code FTS2200289

Name SHARP REFRACTIVE TRIM 12 UNIT 3000K WF NRO + SHARP REFRACTIVE KIT LOUVRES 3 UNIT NRO

Luminaire Flux	3066 lm	Luminaire Power	24.0 W	Efficacy	127.754 lm/W	Efficiency	100.00%
Source Flux	3066 lm	Maximum value	1156.50 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	460 mm	Width	55 mm	Height	55 mm
Rectangular Luminous Area		Length	420 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.014700 m2		Emitting area on Plane 180°	0.000000 m2		
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°	0.000000 m2		
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°	0.003556 m2		
Coordinate system		CG		Symmetry Type	Double Symmetrical		
Date		04-10-2022		Maximum Gamma Angle	180		
Measurement Distance		0.00		Measurement Flux	3066 lm		


LED Flux=3811lm LED Power=24W Eff=80% EfcLed=159lm/W EfcLum=128lm/W CCT=3000K Ra=90 SDCM=3 L70(6K)=50000h

C.I.E. 98 100 100 100 100  
F UTE --

D DIN 5040  
B NBN

A60  
BZ 1

460mm x 55mm



Semipiani C

180.0 — 0.0  
270.0 — 90.0

ULOR 0.00 %  
DLOR 100.00 %  
RN 0.00 %

