

## Luminaire

Code CE16101+BZ07404

Name SHARP REFRACTIVE TRIM 16 UNIT 3000K WF BCO + SHARP REFRACTIVE KIT LOUVRES 4 UNIT NRO

## Measurement

Code FTS2200290

Name SHARP REFRACTIVE TRIM 16 UNIT 3000K WF BCO + SHARP REFRACTIVE KIT LOUVRES 4 UNIT NRO

Luminaire Flux	4088 lm	Luminaire Power	32.0 W	Efficacy	127.754 lm/W	Efficiency	100.00%
Source Flux	4088 lm	Maximum value	1156.50 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	608 mm	Width	55 mm	Height	55 mm
Rectangular Luminous Area		Length	560 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.019600 m <sup>2</sup>		Emitting area on Plane 180°		0.000000 m <sup>2</sup>	
Emitting area on Plane 0°		0.000000 m <sup>2</sup>		Emitting area on Plane 270°		0.000000 m <sup>2</sup>	
Emitting area on Plane 90°		0.000000 m <sup>2</sup>		Glare area at 76°		0.004742 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		04-10-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4088 lm	


LED Flux=5081lm LED Power=32W Eff=80% EfcLed=159lm/W EfcLum=128lm/W CCT=3000K Ra=90 SDCM=3 L70(6K)=50000h

C.I.E. 98 100 100 100 100  
F UTE --

D DIN 5040  
B NBN

A60  
BZ 1

608mm x 55mm



Semipiani C

180.0 — 0.0  
270.0 — 90.0

ULOR 0.00 %  
DLOR 100.00 %  
RN 0.00 %

