

## Luminaire

Code CE16304+BZ07401  
 Name SHARP REFRACTIVE TRIM 16 UNIT 4000K WF NRO + SHARP REFRACTIVE KIT LOUVRES 4 UNIT BCO

## Measurement

Code FTS2200278-A  
 Name SHARP REFRACTIVE TRIM 16 UNIT 4000K WF NRO + SHARP REFRACTIVE KIT LOUVRES 4 UNIT BCO

Luminaire Flux	4855 lm	Luminaire Power	32.0 W	Efficacy	151.719 lm/W	Efficiency	100.00%
Source Flux	4855 lm	Maximum value	1066.40 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	608 mm	Width	55 mm	Height	55 mm
Rectangular Luminous Area		Length	560 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.019600 m <sup>2</sup>		Emitting area on Plane 180°		0.000000 m <sup>2</sup>	
Emitting area on Plane 0°		0.000000 m <sup>2</sup>		Emitting area on Plane 270°		0.000000 m <sup>2</sup>	
Emitting area on Plane 90°		0.000000 m <sup>2</sup>		Glare area at 76°		0.004742 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		29-09-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4855 lm	


LED Flux=5364lm LED Power=32W Eff=91% EfcLed=168lm/W EfcLum=152lm/W CCT=4000K Ra=90 SDCM=3 L70(6K)=50000h

C.I.E. 92 97 99 100 100  
 F UTE 1.00 A

D DIN 5040  
 B NBN

A60  
 BZ 1

608mm x 55mm



Semipiani C

180.0 — 0.0  
 270.0 — 90.0

ULOR 0.00 %  
 DLOR 100.00 %  
 RN 0.00 %

