

## Luminaire

Code CE16305+BZ07404  
 Name SHARP REFRACTIVE TRIM 16 UNIT 4000K WF SIL + SHARP REFRACTIVE KIT LOUVRES 4 UNIT NRO

## Measurement

Code FTS2200294-A  
 Name SHARP REFRACTIVE TRIM 16 UNIT 4000K WF SIL + SHARP REFRACTIVE KIT LOUVRES 4 UNIT NRO

Luminaire Flux	4316 lm	Luminaire Power	32.0 W	Efficacy	134.875 lm/W	Efficiency	100.00%
Source Flux	4316 lm	Maximum value	1156.50 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	608 mm	Width	55 mm	Height	55 mm
Rectangular Luminous Area		Length	560 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.019600 m <sup>2</sup>		Emitting area on Plane 180°		0.000000 m <sup>2</sup>	
Emitting area on Plane 0°		0.000000 m <sup>2</sup>		Emitting area on Plane 270°		0.000000 m <sup>2</sup>	
Emitting area on Plane 90°		0.000000 m <sup>2</sup>		Glare area at 76°		0.004742 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		29-09-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4316 lm	
LED Flux=5364lm LED Power=32W Eff=80% EfcLed=168lm/W EfcLum=135lm/W CCT=4000K Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	98	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1



