

Luminaire


Code CE16404IN0+BZ07401
 Name SHARP REFRACTIVE TRIM 16 UNIT WI WF NRO + SHARP REFRACTIVE KIT LOUVRES 4 UNIT BC0

Measurement

Code FTS2200282-A
 Name SHARP REFRACTIVE TRIM 16 UNIT WI WF NRO + SHARP REFRACTIVE KIT LOUVRES 4 UNIT BC0

Luminaire Flux	4784 lm	Luminaire Power	32.0 W	Efficacy	149.485 lm/W	Efficiency	100.00%
Source Flux	4784 lm	Maximum value	1066.40 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	608 mm	Width	55 mm	Height	55 mm
Rectangular Luminous Area		Length	560 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.019600 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.004742 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		08-02-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4784 lm	
LED Flux=5285lm LED Power=32W Eff=91% EfcLed=165lm/W EfcLum=149lm/W CCT=5000K Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	92 97 99 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

608mm x 55mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 0.00 %
 DLOR 100.00 %
 RN 0.00 %

