

Luminaire


Code CM110101
Name A.39 MICRO REFR.1184 DI/IN 930 DAL BC/BC

Measurement

Code FTS2400083
Name A.39 MICRO REFR.1184 DI/IN 930 DAL BC/BC

Luminaire Flux	5264 lm	Luminaire Power	36.0 W	Efficacy	146.222 lm/W	Efficiency	100.00%
Source Flux	5264 lm	Maximum value	528.69 cd/klm	Position	C=90.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1184 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	1088 mm	Width	34 mm	Height	0 mm
Horizontal Luminous Area		0.036992 m ²		Emitting area on Plane 180°	0.000000 m ²		
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°	0.000000 m ²		
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°	0.008949 m ²		
Coordinate system		CG		Symmetry Type	Double Symmetrical		
Date		25-03-2024		Maximum Gamma Angle	180		
Measurement Distance		0.00		Measurement Flux	5264 lm		
LED Flux=5802lm LED Power=31W Eff=91% EfcLed=189lm/W EfcLum=146lm/W CCT=3000K Ra=90 SDCM=3 L70(17k)=102000h							
C.I.E.	93 97 99 60 100			D DIN 5040	C61		
F UTE	0.60 A + 0.40 T			B NBN	BZ 1		

1184mm x 45mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 40.08 %

DLOR 59.92 %

RN 40.08 %

