

Luminaire

Code CM510104
Name A.39 MICRO REFR.2960 DI/IN 930 DAL NR/NR

Measurement

Code FTS2400090
Name A.39 MICRO REFR.2960 DI/IN 930 DAL NR/NR

Luminaire Flux	12360 lm	Luminaire Power	86.0 W	Efficacy	143.721 lm/W	Efficiency	100.00%
Source Flux	12360 lm	Maximum value	523.76 cd/klm	Position	C=70.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2960 mm	Width	45 mm	Height	85 mm
Rectangular Luminous Area		Length	2720 mm	Width	34 mm	Height	0 mm
Horizontal Luminous Area		0.092480 m2		Emitting area on Plane 180°	0.000000 m2		
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°	0.000000 m2		
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°	0.022373 m2		
Coordinate system		CG		Symmetry Type	Double Symmetrical		
Date		25-03-2024		Maximum Gamma Angle	180		
Measurement Distance		0.00		Measurement Flux	12360 lm		


LED Flux=14919lm LED Power=79W Eff=83% EfcLed=189lm/W EfcLum=144lm/W CCT=3000K Ra=90 SDCM=3 L70(17k)=102000h

C.I.E. 100 100 100 57 100
F UTE --

D DIN 5040
B NBN

C61
BZ 1

2960mm x 45mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 43.23 %

DLOR 56.77 %

RN 43.23 %

