

Luminaire

Code FU50104
Name VECTOR 55 PENDANT FUNIVIA 927 FL NRO

Measurerm.

Code FTS1801587-B
Name VECTOR 55 PENDANT FUNIVIA 927 FL NRO

| | | | | | | | |
|--|---------|-----------------|----------------|-----------------------------|---------------|-----------------|-----------------|
| Luminaire Flux | 1715 lm | Luminaire Power | 19.0 W | Efficacy | 90.263 lm/W | Efficiency | 100.00% |
| Source Flux | 1715 lm | Maximum value | 5145.51 cd/klm | Position | C=0.00 G=0.00 | CG | Rotosymmetrical |
| Round Luminaire | | Diam. | 55 mm | Height | 130 mm | | |
| Round Luminous Area | | Diam. | 48 mm | Height | 0 mm | | |
| Horizontal Luminous Area | | 0.001810 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.000438 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Rotosymmetrical | |
| Date | | 29-02-2024 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 1715 lm | |
| LED Flux=2359lm LED Power=17W Eff=73% EfcLed=136lm/W EfcLum=90lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(9k)=50000h | | | | | | | |
| C.I.E. | 99 | 100 | 100 | 100 | D DIN 5040 | A60 | |
| F UTE | -- | | | | B NBN | BZ 1 | |

Diam=55mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code FU50104
Name VECTOR 55 PENDANT FUNIVIA 927 FL NRO

Measurerm.


Code FTS1801587-B
Name VECTOR 55 PENDANT FUNIVIA 927 FL NRO

| | | | | | | | |
|--|---------|-----------------|----------------|-----------------------------|---------------|-----------------|-----------------|
| Luminaire Flux | 1715 lm | Luminaire Power | 19.0 W | Efficacy | 90.263 lm/W | Efficiency | 100.00% |
| Source Flux | 1715 lm | Maximum value | 5145.51 cd/klm | Position | C=0.00 G=0.00 | CG | Rotosymmetrical |
| Round Luminaire | | Diam. | 55 mm | Height | 130 mm | | |
| Round Luminous Area | | Diam. | 48 mm | Height | 0 mm | | |
| Horizontal Luminous Area | | 0.001810 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.000438 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Rotosymmetrical | |
| Date | | 29-02-2024 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 1715 lm | |
| LED Flux=2359lm LED Power=17W Eff=73% EfcLed=136lm/W EfcLum=90lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(9k)=50000h | | | | | | | |
| C.I.E. | 99 | 100 | 100 | 100 | 100 | D DIN 5040 | A60 |
| F UTE | -- | | | | | B NBN | BZ 1 |

Width at 50.00 % of Max Intensity

| H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 | H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 |
|------|------|------|------|------|------|------|------|------|------|------|------|
| OA | 0.20 | 0.41 | 0.61 | 0.81 | 1.01 | OC | 0.20 | 0.41 | 0.61 | 0.81 | 1.01 |
| OB | 0.20 | 0.41 | 0.61 | 0.81 | 1.01 | OD | 0.20 | 0.41 | 0.61 | 0.81 | 1.01 |

| | Luminous Intensities [cd/klm] | | | | | | | | | |
|----|---------------------------------|---------|---------|--------|-------|------|------|------|------|------|
| | 0 | 5 | 15 | 25 | 35 | 45 | 55 | 65 | 75 | 85 |
| OA | 8824.54 | 8020.86 | 2480.66 | 626.85 | 17.32 | 6.30 | 3.07 | 1.85 | 1.03 | 0.39 |
| OB | 8824.54 | 8020.86 | 2480.66 | 626.85 | 17.32 | 6.30 | 3.07 | 1.85 | 1.03 | 0.39 |
| OC | 8824.54 | 8020.86 | 2480.66 | 626.85 | 17.32 | 6.30 | 3.07 | 1.85 | 1.03 | 0.39 |
| OD | 8824.54 | 8020.86 | 2480.66 | 626.85 | 17.32 | 6.30 | 3.07 | 1.85 | 1.03 | 0.39 |



| H[m] | D[m] | Max lux | Med lux | Alpha=11.5°+11.5° | G=0.0 |
|------|------|---------|---------|-------------------|-------|
| 1.00 | 0.41 | 8825 | 5686 | | |
| 2.00 | 0.81 | 2206 | 1421 | | |
| 3.00 | 1.22 | 981 | 632 | | |
| 4.00 | 1.62 | 552 | 355 | | |
| 5.00 | 2.03 | 353 | 227 | | |