


Luminaire

Code FU70001APP
Name SHARPING 12 FUNIVIA 927 FL BCO

Measurement

Code FTS2200029
Name SHARPING 12 FUNIVIA 927 FL BCO

Luminaire Flux	2100 lm	Luminaire Power	25.0 W	Efficacy	84.005 lm/W	Efficiency	100.00%
Source Flux	2100 lm	Maximum value	2814.46 cd/klm	Position	C=20.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	465 mm	Width	28 mm	Height	20 mm
Rectangular Luminous Area		Length	240 mm	Width	20 mm	Height	0 mm
Horizontal Luminous Area		0.004800 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.001161 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		15-02-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2100 lm	
LED Flux=2580lm LED Power=24W Eff=81% EfcLed=109lm/W EfcLum=84lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(6K)=36000h							
C.I.E.	98 100 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		



Luminaire

Code FU70001APP
Name SHARPING 12 FUNIVIA 927 FL BCO

Measurment


Code FTS2200029
Name SHARPING 12 FUNIVIA 927 FL BCO

Luminaire Flux	2100 lm	Luminaire Power	25.0 W	Efficacy	84.005 lm/W	Efficiency	100.00%
Source Flux	2100 lm	Maximum value	2814.46 cd/klm	Position	C=20.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	465 mm	Width	28 mm	Height	20 mm
Rectangular Luminous Area		Length	240 mm	Width	20 mm	Height	0 mm
Horizontal Luminous Area		0.004800 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.001161 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		15-02-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2100 lm	
LED Flux=2580lm LED Power=24W Eff=81% EfcLed=109lm/W EfcLum=84lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(6K)=36000h							
C.I.E.	98	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.24	0.47	0.71	0.95	1.18	OC	0.25	0.50	0.75	1.00	1.25
OB	0.24	0.47	0.71	0.95	1.18	OD	0.25	0.50	0.75	1.00	1.25

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	5847.03	5307.69	2458.89	984.12	558.13	13.99	4.85	1.39	0.00	0.00
OB	5847.03	5307.69	2458.89	984.12	558.13	13.99	4.85	1.39	0.00	0.00
OC	5847.03	5525.12	2681.73	1063.96	551.34	20.40	5.61	1.33	0.00	0.00
OD	5847.03	5525.12	2681.73	1063.96	551.34	20.40	5.61	1.33	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=13.3°+13.3°	G=0.0 Max non a G
1.00	0.47	5908	3646		
2.00	0.95	1477	911		
3.00	1.42	656	405		
4.00	1.89	369	228		
5.00	2.37	236	146		

H[m]	D[m]	Max lux	Med lux	Beta=14.1°+14.1°	G=0.0 Max non a G
1.00	0.50	5908	3646		
2.00	1.00	1477	911		
3.00	1.50	656	405		
4.00	2.01	369	228		
5.00	2.51	236	146		