

Luminaire

Code FU71104APP
Name SHARPING 12 FUNIVIA 930 XF NRO

Measurement

Code FTS2200032
Name SHARPING 12 FUNIVIA 930 XF NRO

Luminaire Flux	2232 lm	Luminaire Power	25.0 W	Efficacy	89.299 lm/W	Efficiency	100.00%
Source Flux	2232 lm	Maximum value	1052.56 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	465 mm	Width	28 mm	Height	20 mm
Rectangular Luminous Area		Length	240 mm	Width	20 mm	Height	0 mm
Horizontal Luminous Area		0.004800 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.001161 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		15-02-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2232 lm	
LED Flux=2580lm LED Power=24W Eff=87% EfcLed=109lm/W EfcLum=89lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(6K)=36000h							
C.I.E.	98	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	



