

## Luminaire


Code KA51117+BZ06104  
 Name Kata metron 2368 ref dir 930 Dali glo + A.39 S/C SHARP REFR KIT LOUVRES 2368 NRO

## Measurement

Code FTS2400470.  
 Name Kata metron 2368 ref dir 930 Dali glo + A.39 S/C SHARP REFR KIT LOUVRES 2368 NRO

Luminaire Flux	8920 lm	Luminaire Power	73.0 W	Efficacy	122.192 lm/W	Efficiency	100.00%
Source Flux	8920 lm	Maximum value	1170.52 cd/klm	Position	C=5.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	100 mm	Height	85 mm
Rectangular Luminous Area		Length	2240 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.078400 m <sup>2</sup>		Emitting area on Plane 180°		0.000000 m <sup>2</sup>	
Emitting area on Plane 0°		0.000000 m <sup>2</sup>		Emitting area on Plane 270°		0.000000 m <sup>2</sup>	
Emitting area on Plane 90°		0.000000 m <sup>2</sup>		Glare area at 76°		0.018967 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		16-04-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		8920 lm	
LED Flux=11086lm LED Power=63W Eff=80% EfcLed=176lm/W EfcLum=122lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E.	98	100	100	100	D DIN 5040	A60	
F UTE	--				B NBN	BZ 1	


2368mm x 100mm



Semipiani C

180.0 — 0.0  
 270.0 — 90.0

ULOR 0.00 %  
 DLOR 100.00 %  
 RN 0.00 %



## Luminaire

Code KA51117+BZ06104  
 Name Kata metron 2368 ref dir 930 Dali glo + A.39 S/C SHARP REFR KIT LOUVRES 2368 NRO

## Measurement

Code FTS2400470.  
 Name Kata metron 2368 ref dir 930 Dali glo + A.39 S/C SHARP REFR KIT LOUVRES 2368 NRO

Luminaire Flux	8920 lm	Luminaire Power	73.0 W	Efficacy	122.192 lm/W	Efficiency	100.00%
Source Flux	8920 lm	Maximum value	1170.52 cd/klm	Position	C=5.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	100 mm	Height	85 mm
Rectangular Luminous Area		Length	2240 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.078400 m2		Emitting area on Plane 180°	0.000000 m2		
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°	0.000000 m2		
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°	0.018967 m2		
Coordinate system		CG		Symmetry Type	Double Symmetrical		
Date		16-04-2024		Maximum Gamma Angle	180		
Measurement Distance		0.00		Measurement Flux	8920 lm		


LED Flux=11086lm LED Power=63W Eff=80% EfcLed=176lm/W EfcLum=122lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)=50000h

C.I.E.	98 100 100 100 100	D DIN 5040	A60
F UTE	--	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.59	1.17	1.76	2.34	2.93	OC	0.59	1.17	1.76	2.35	2.93
OB	0.59	1.17	1.76	2.34	2.93	OD	0.59	1.17	1.76	2.35	2.93

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	10439.73	10296.04	9229.50	7327.29	2362.16	74.13	15.09	3.43	2.29	1.80
OB	10439.73	10296.04	9229.50	7327.29	2362.16	74.13	15.09	3.43	2.29	1.80
OC	10439.73	10321.90	9265.84	7302.79	2503.62	78.24	16.94	3.75	2.40	1.88
OD	10439.73	10321.90	9265.84	7302.79	2503.62	78.24	16.94	3.75	2.40	1.88



H[m]	D[m]	Max lux	Med lux	Alpha=30.3°+30.3°	G=0.0
1.00	1.17	10440	5507		
2.00	2.34	2610	1377		
3.00	3.51	1160	612		
4.00	4.68	652	344		
5.00	5.85	418	220		

H[m]	D[m]	Max lux	Med lux	Beta=30.4°+30.4°	G=0.0
1.00	1.17	10440	5507		
2.00	2.35	2610	1377		
3.00	3.52	1160	612		
4.00	4.69	652	344		
5.00	5.86	418	220		