

Luminaire


Code KB53109+BZ06104
 Name Kata metron 2368 ref dir in 940 Dali vde + A.39 S/C SHARP REFR KIT LOUVRES 2368 NRO

Measurement

Code FTS2400479.
 Name Kata metron 2368 ref dir in 940 Dali vde + A.39 S/C SHARP REFR KIT LOUVRES 2368 NRO

Luminaire Flux	14176 lm	Luminaire Power	104.0 W	Efficacy	136.308 lm/W	Efficiency	100.00%
Source Flux	14176 lm	Maximum value	785.58 cd/klm	Position	C=5.00 G=1.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	100 mm	Height	85 mm
Rectangular Luminous Area		Length	2240 mm	Width	35 mm	Height	0 mm
Horizontal Luminous Area		0.078400 m ²		Emitting area on Plane 180°		0.000000 m ²	
Emitting area on Plane 0°		0.000000 m ²		Emitting area on Plane 270°		0.000000 m ²	
Emitting area on Plane 90°		0.000000 m ²		Glare area at 76°		0.018967 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		16-04-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		14176 lm	
LED Flux=17401lm LED Power=93W Eff=81% EfcLed=187lm/W EfcLum=136lm/W CCT=4000K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E.	98	100	100	67	100	D DIN 5040	B61
F UTE	--					B NBN	BZ 1

2368mm x 100mm



Semipiani C

180.0 — 0.0
 270.0 — 90.0

ULOR 32.89 %
 DLOR 67.11 %
 RN 32.89 %

