

Luminaire

Code KZ21204
Name kata metron pst pen 1x40 Dali 930 WF nr

Measurement

Code FTS2400408.
Name kata metron pst pen 1x40 Dali 930 WF nr

Luminaire Flux	542 lm	Luminaire Power	11.0 W	Efficacy	49.273 lm/W	Efficiency	100.00%
Source Flux	542 lm	Maximum value	3590.26 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Round Luminous Area		Length Diam.	40 mm 33 mm	Width Height	40 mm 0 mm	Height	103 mm
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.000855 m2 0.000000 m2 0.000000 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.000000 m2 0.000000 m2 0.000207 m2	
Coordinate system Date Measurement Distance		CG 21-06-2024 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 542 lm	
LED Flux=867lm LED Power=8W Eff=62% EfcLed=110lm/W EfcLum=49lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(9k)=50000h							
C.I.E. F UTE	98 100 100 100 100 --			D DIN 5040 B NBN	A60 BZ 1		


40mm x 40mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
DLOR 100.00 %
RN 0.00 %



Luminaire

Code KZ21204
 Name kata metron pst pen 1x40 Dali 930 WF nr
Measurment.
 Code FTS2400408.
 Name kata metron pst pen 1x40 Dali 930 WF nr

Luminaire Flux	542 lm	Luminaire Power	11.0 W	Efficacy	49.273 lm/W	Efficiency	100.00%
Source Flux	542 lm	Maximum value	3590.26 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Round Luminous Area		Length Diam.	40 mm 33 mm	Width Height	40 mm 0 mm	Height	103 mm
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.000855 m2 0.000000 m2 0.000000 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.000000 m2 0.000000 m2 0.000207 m2	
Coordinate system Date Measurement Distance		CG 21-06-2024 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 542 lm	


LED Flux=867lm LED Power=8W Eff=62% EfcLed=110lm/W EfcLum=49lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(9k)=50000h

C.I.E. F UTE	98 100 100 100 100 --	D DIN 5040 B NBN	A60 BZ 1
-----------------	--------------------------	---------------------	-------------

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.25	0.49	0.74	0.99	1.24	OC	0.25	0.49	0.74	0.99	1.24
OB	0.25	0.49	0.74	0.99	1.24	OD	0.25	0.49	0.74	0.99	1.24

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1945.92	1786.42	862.21	224.09	45.84	10.15	2.60	0.45	0.00	0.00
OB	1945.92	1786.42	862.21	224.09	45.84	10.15	2.60	0.45	0.00	0.00
OC	1945.92	1786.42	862.21	224.09	45.84	10.15	2.60	0.45	0.00	0.00
OD	1945.92	1786.42	862.21	224.09	45.84	10.15	2.60	0.45	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=13.9°+13.9°	G=0.0
1.00	0.49	1946	1204		
2.00	0.99	486	301		
3.00	1.48	216	134		
4.00	1.98	122	75		
5.00	2.47	78	48		