

Luminaire

Code KZ30204+AP91300
 Name kata metron pst spot 1x55 Dali 927 WL nr + Soft Filter

Measurement

Code FTS2400327.
 Name kata metron pst spot 1x55 Dali 927 WL nr + Soft Filter

Luminaire Flux	1496 lm	Luminaire Power	22.0 W	Efficacy	68.000 lm/W	Efficiency	100.00%
Source Flux	1496 lm	Maximum value	3005.49 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Round Luminous Area	Length Diam.	55 mm 48 mm	Width Height	55 mm 0 mm	Height	130 mm	
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°	0.001810 m2 0.000000 m2 0.000000 m2	Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°	0.000000 m2 0.000000 m2 0.000438 m2				
Coordinate system Date Measurement Distance	CG 20-06-2024 0.00	Symmetry Type Maximum Gamma Angle Measurement Flux	Rotosymmetrical 180 1496 lm				
LED Flux=2404lm LED Power=18W Eff=62% EfcLed=137lm/W EfcLum=68lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E. F UTE	97 99 100 100 100 --	D DIN 5040 B NBN	A60 BZ 1				


55mm x 55mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
 DLOR 100.00 %
 RN 0.00 %



Luminaire

Code KZ30204+AP91300
Name kata metron pst spot 1x55 Dali 927 WL nr + Soft Filter

Measurement


Code FTS2400327.
Name kata metron pst spot 1x55 Dali 927 WL nr + Soft Filter

Luminaire Flux	1496 lm	Luminaire Power	22.0 W	Efficacy	68.000 lm/W	Efficiency	100.00%
Source Flux	1496 lm	Maximum value	3005.49 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Round Luminous Area		Length Diam.	55 mm 48 mm	Width Height	55 mm 0 mm	Height	130 mm
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.001810 m2 0.000000 m2 0.000000 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.000000 m2 0.000000 m2 0.000438 m2	
Coordinate system Date Measurement Distance		CG 20-06-2024 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 1496 lm	
LED Flux=2404lm LED Power=18W Eff=62% EfcLed=137lm/W EfcLum=68lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E. F UTE	97 99 100 100 100 --			D DIN 5040 B NBN	A60 BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.28	0.56	0.84	1.12	1.40	OC	0.28	0.56	0.84	1.12	1.40
OB	0.28	0.56	0.84	1.12	1.40	OD	0.28	0.56	0.84	1.12	1.40

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	4496.21	4208.98	2382.52	696.44	137.65	29.50	10.19	6.74	4.07	0.94
OB	4496.21	4208.98	2382.52	696.44	137.65	29.50	10.19	6.74	4.07	0.94
OC	4496.21	4208.98	2382.52	696.44	137.65	29.50	10.19	6.74	4.07	0.94
OD	4496.21	4208.98	2382.52	696.44	137.65	29.50	10.19	6.74	4.07	0.94



H[m]	D[m]	Max lux	Med lux	Alpha=15.6°+15.6°	G=0.0
1.00	0.56	4496	2755		
2.00	1.12	1124	689		
3.00	1.68	500	306		
4.00	2.24	281	172		
5.00	2.80	180	110		