

Luminaire

Code M250021
Name TAGORA 970 INC. LED DIMM. DALI 3000K BIANCO

Measurem.

Code FTS2300135
Name TAGORA 970 INC. LED DIMM. DALI 3000K BIANCO

Luminaire Flux	6630 lm	Luminaire Power	84.0 W	Efficacy	78.923 lm/W	Efficiency	100.00%
Source Flux	6630 lm	Maximum value	368.66 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	970 mm	Height	235 mm		
Round Luminous Area		Diam.	830 mm	Height	0 mm		
Horizontal Luminous Area			0.541061 m2	Emitting area on Plane 180°			0.000000 m2
Emitting area on Plane 0°			0.000000 m2	Emitting area on Plane 270°			0.000000 m2
Emitting area on Plane 90°			0.000000 m2	Glare area at 76°			0.130894 m2
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		30-05-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		6630 lm	
LED Flux=12819lm LED Power=74W Eff=52% EfcLed=173lm/W EfcLum=79lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=70000h							
C.I.E.	49 82 97 100 100			D DIN 5040	A30		
F UTE	1.00 E			B NBN	BZ 4		

Diam=970mm




Semipiani C

180.0 ——— 0.0

ULOR 0.01 %

DLOR 99.99 %

RN 0.01 %



Luminaire

Code M250021
Name TAGORA 970 INC. LED DIMM. DALI 3000K BIANCO

Measurem.

Code FTS2300135
Name TAGORA 970 INC. LED DIMM. DALI 3000K BIANCO

Luminaire Flux	6630 lm	Luminaire Power	84.0 W	Efficacy	78.923 lm/W	Efficiency	100.00%
Source Flux	6630 lm	Maximum value	368.66 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	970 mm	Height	235 mm		
Round Luminous Area		Diam.	830 mm	Height	0 mm		
Horizontal Luminous Area		0.541061 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.130894 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		30-05-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		6630 lm	


LED Flux=12819lm LED Power=74W Eff=52% EfcLed=173lm/W EfcLum=79lm/W CCT=3000K Ra=80 SDCM=3 L70(6K)=70000h

C.I.E.	49 82 97 100 100	D DIN 5040	A30
F UTE	1.00 E	B NBN	BZ 4

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.42	2.83	4.25	5.67	7.08	OC	1.42	2.83	4.25	5.67	7.08
OB	1.42	2.83	4.25	5.67	7.08	OD	1.42	2.83	4.25	5.67	7.08

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	2444.02	2433.11	2346.26	2176.94	1932.08	1603.78	1212.90	785.31	352.88	36.89
OB	2444.02	2433.11	2346.26	2176.94	1932.08	1603.78	1212.90	785.31	352.88	36.89
OC	2444.02	2433.11	2346.26	2176.94	1932.08	1603.78	1212.90	785.31	352.88	36.89
OD	2444.02	2433.11	2346.26	2176.94	1932.08	1603.78	1212.90	785.31	352.88	36.89



H[m]	D[m]	Max lux	Med lux	Alpha=54.8°+54.8°	G=0.0
1.00	2.83	2444	636		
2.00	5.67	611	159		
3.00	8.50	272	71		
4.00	11.33	153	40		
5.00	14.17	98	25		