

Luminaire

Code M251425_0°
Name EVERYT 80 RD OR LED 3000K 2X22° B/B_0°

Measurement

Code FTS2400200.
Name EVERYT 80 RD OR LED 3000K 2X22° B/B_0°

Luminaire Flux	990 lm	Luminaire Power	10.0 W	Efficacy	99.000 lm/W	Efficiency	100.00%
Source Flux	990 lm	Maximum value	1192.24 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	80 mm	Height	115 mm		
Round Luminous Area		Diam.	60 mm	Height	0 mm		
Horizontal Luminous Area			0.002827 m2	Emitting area on Plane 180°			0.000000 m2
Emitting area on Plane 0°			0.000000 m2	Emitting area on Plane 270°			0.000000 m2
Emitting area on Plane 90°			0.000000 m2	Glare area at 76°			0.000684 m2
Coordinate system		CG		Symmetry Type			Rotosymmetrical
Date		22-05-2024		Maximum Gamma Angle			180
Measurement Distance		0.00		Measurement Flux			990 lm

LED Flux=1556lm LED Power=10W Eff=64% EfcLed=156lm/W EfcLum=99lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)=50000h

C.I.E. 79 93 99 100 100
F UTE 1.00 B

D DIN 5040
B NBN
A60
BZ 1

Diam=80mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code M251425_0°
 Name EVERYT 80 RD OR LED 3000K 2X22° B/B_0°
Measurement.
 Code FTS2400200.
 Name EVERYT 80 RD OR LED 3000K 2X22° B/B_0°

Luminaire Flux	990 lm	Luminaire Power	10.0 W	Efficacy	99.000 lm/W	Efficiency	100.00%
Source Flux	990 lm	Maximum value	1192.24 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	80 mm	Height	115 mm		
Round Luminous Area		Diam.	60 mm	Height	0 mm		
Horizontal Luminous Area		0.002827 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000684 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		22-05-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		990 lm	


LED Flux=1556lm LED Power=10W Eff=64% EfcLed=156lm/W EfcLum=99lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)=50000h

C.I.E.	79 93 99 100 100	D DIN 5040	A60
F UTE	1.00 B	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.44	0.88	1.32	1.75	2.19	OC	0.44	0.88	1.32	1.75	2.19
OB	0.44	0.88	1.32	1.75	2.19	OD	0.44	0.88	1.32	1.75	2.19

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1180.32	1135.27	880.82	542.10	270.30	117.85	69.98	40.67	20.01	5.55
OB	1180.32	1135.27	880.82	542.10	270.30	117.85	69.98	40.67	20.01	5.55
OC	1180.32	1135.27	880.82	542.10	270.30	117.85	69.98	40.67	20.01	5.55
OD	1180.32	1135.27	880.82	542.10	270.30	117.85	69.98	40.67	20.01	5.55



H[m]	D[m]	Max lux	Med lux	Alpha=23.7°+23.7°	G=0.0
1.00	0.88	1180	653		
2.00	1.75	295	163		
3.00	2.63	131	73		
4.00	3.51	74	41		
5.00	4.39	47	26		