

## Luminaire

Code M251820  
Name EVERYT 80 RD FI LED 3000K 2X14° N/B

## Measurerm.

Code FTS1602123-A  
Name EVERYT 80 RD FI LED 3000K 2X14° N/B

Luminaire Flux	962 lm	Luminaire Power	10.0 W	Efficacy	96.200 lm/W	Efficiency	100.00%
Source Flux	962 lm	Maximum value	2927.39 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	80 mm	Height	115 mm		
Round Luminous Area		Diam.	60 mm	Height	0 mm		
Horizontal Luminous Area			0.002827 m2	Emitting area on Plane 180°			0.000000 m2
Emitting area on Plane 0°			0.000000 m2	Emitting area on Plane 270°			0.000000 m2
Emitting area on Plane 90°			0.000000 m2	Glare area at 76°			0.000684 m2
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		20-05-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		962 lm	
LED Flux=1556lm LED Power=10W Eff=62% EfcLed=156lm/W EfcLum=96lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E.	98 100 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		


Diam=80mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %  
DLOR100.00 %  
RN 0.00 %



## Luminaire

Code M251820  
Name EVERYT 80 RD FI LED 3000K 2X14° N/B

## Measurum.


Code FTS1602123-A  
Name EVERYT 80 RD FI LED 3000K 2X14° N/B

Luminaire Flux	962 lm	Luminaire Power	10.0 W	Efficacy	96.200 lm/W	Efficiency	100.00%
Source Flux	962 lm	Maximum value	2927.39 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	80 mm	Height	115 mm		
Round Luminous Area		Diam.	60 mm	Height	0 mm		
Horizontal Luminous Area		0.002827 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000684 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		20-05-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		962 lm	
LED Flux=1556lm LED Power=10W Eff=62% EfcLed=156lm/W EfcLum=96lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E.	98 100 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

### Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.28	0.55	0.83	1.10	1.38	OC	0.28	0.55	0.83	1.10	1.38
OB	0.28	0.55	0.83	1.10	1.38	OD	0.28	0.55	0.83	1.10	1.38

	Luminous Intensities [ cd/klm ]									
	0	5	15	25	35	45	55	65	75	85
OA	2816.15	2577.03	1456.33	500.08	120.73	18.50	4.56	0.77	0.37	0.24
OB	2816.15	2577.03	1456.33	500.08	120.73	18.50	4.56	0.77	0.37	0.24
OC	2816.15	2577.03	1456.33	500.08	120.73	18.50	4.56	0.77	0.37	0.24
OD	2816.15	2577.03	1456.33	500.08	120.73	18.50	4.56	0.77	0.37	0.24



H[m]	D[m]	Max lux	Med lux	Alpha=15.4°+15.4°	G=0.0
1.00	0.55	2816	1697		
2.00	1.10	704	424		
3.00	1.66	313	189		
4.00	2.21	176	106		
5.00	2.76	113	68		