

Luminaire

Code M254605_0°
Name EVERYT 80 SQ OR TS LED3000K 2X9° B_0°

Measurem.

Code FTS2400201.
Name EVERYT 80 SQ OR TS LED3000K 2X9° B_0°

Luminaire Flux	1128 lm	Luminaire Power	10.0 W	Efficacy	112.800 lm/W	Efficiency	100.00%
Source Flux	1128 lm	Maximum value	3125.77 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire	Length	80 mm	Width	80 mm	Height	115 mm	
Rectangular Luminous Area	Length	60 mm	Width	60 mm	Height	0 mm	
Horizontal Luminous Area	0.003600 m2	Emitting area on Plane 180°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2	Emitting area on Plane 90°	0.000871 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical	Maximum Gamma Angle	180	Measurement Distance	1128 lm
Date	22-05-2024	Measurement Flux	1128 lm				
LED Flux=1556lm LED Power=10W Eff=72% EfcLed=156lm/W EfcLum=113lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E.	89 96 99 100 100	D DIN 5040	A60				
F UTE	1.00 A	B NBN	BZ 1				

80mm x 80mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code M254605_0°
Name EVERYT 80 SQ OR TS LED3000K 2X9° B_0°

Measurerm.


Code FTS2400201.
Name EVERYT 80 SQ OR TS LED3000K 2X9° B_0°

Luminaire Flux	1128 lm	Luminaire Power	10.0 W	Efficacy	112.800 lm/W	Efficiency	100.00%
Source Flux	1128 lm	Maximum value	3125.77 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	80 mm	Width	80 mm	Height	115 mm
Rectangular Luminous Area		Length	60 mm	Width	60 mm	Height	0 mm
Horizontal Luminous Area		0.003600 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000871 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		22-05-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1128 lm	
LED Flux=1556lm LED Power=10W Eff=72% EfcLed=156lm/W EfcLum=113lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E.	89 96 99 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.21	0.43	0.64	0.86	1.07	OC	0.21	0.43	0.64	0.86	1.07
OB	0.21	0.43	0.64	0.86	1.07	OD	0.21	0.43	0.64	0.86	1.07

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	3525.87	2955.01	1350.39	536.36	180.33	65.59	39.13	26.44	15.83	5.01
OB	3525.87	2955.01	1350.39	536.36	180.33	65.59	39.13	26.44	15.83	5.01
OC	3525.87	2955.01	1350.39	536.36	180.33	65.59	39.13	26.44	15.83	5.01
OD	3525.87	2955.01	1350.39	536.36	180.33	65.59	39.13	26.44	15.83	5.01



H[m]	D[m]	Max lux	Med lux	Alpha=12.1°+12.1°	G=0.0
1.00	0.43	3526	2129		
2.00	0.86	881	532		
3.00	1.29	392	237		
4.00	1.72	220	133		
5.00	2.15	141	85		