

Luminaire

Code M279020
Name EVERY 80 RD FI LED 3000K 2X22° M/B

Measurerm.

Code FTS1602153-A
Name EVERY 80 RD FI LED 3000K 2X22° M/B

Luminaire Flux	974 lm	Luminaire Power	10.0 W	Efficacy	97.400 lm/W	Efficiency	100.00%
Source Flux	974 lm	Maximum value	1237.62 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	80 mm	Height	115 mm		
Round Luminous Area		Diam.	60 mm	Height	0 mm		
Horizontal Luminous Area			0.002827 m2	Emitting area on Plane 180°			0.000000 m2
Emitting area on Plane 0°			0.000000 m2	Emitting area on Plane 270°			0.000000 m2
Emitting area on Plane 90°			0.000000 m2	Glare area at 76°			0.000684 m2
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		20-05-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		974 lm	
LED Flux=1556lm LED Power=10W Eff=63% EfcLed=156lm/W EfcLum=97lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E.	86 100 100 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Diam=80mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code M279020
Name EVERY 80 RD FI LED 3000K 2X22° M/B

Measurem.

Code FTS1602153-A
Name EVERY 80 RD FI LED 3000K 2X22° M/B

Luminaire Flux	974 lm	Luminaire Power	10.0 W	Efficacy	97.400 lm/W	Efficiency	100.00%
Source Flux	974 lm	Maximum value	1237.62 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	80 mm	Height	115 mm		
Round Luminous Area		Diam.	60 mm	Height	0 mm		
Horizontal Luminous Area		0.002827 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000684 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		20-05-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		974 lm	

LED Flux=1556lm LED Power=10W Eff=63% EfcLed=156lm/W EfcLum=97lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)=50000h


C.I.E. 86 100 100 100 100
F UTE 1.00 A

D DIN 5040
B NBN
A60
BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.44	0.87	1.31	1.74	2.18	OC	0.44	0.87	1.31	1.74	2.18
OB	0.44	0.87	1.31	1.74	2.18	OD	0.44	0.87	1.31	1.74	2.18

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1205.45	1172.75	896.48	557.52	318.82	162.71	36.55	0.55	0.32	0.26
OB	1205.45	1172.75	896.48	557.52	318.82	162.71	36.55	0.55	0.32	0.26
OC	1205.45	1172.75	896.48	557.52	318.82	162.71	36.55	0.55	0.32	0.26
OD	1205.45	1172.75	896.48	557.52	318.82	162.71	36.55	0.55	0.32	0.26



H[m]	D[m]	Max lux	Med lux	Alpha=23.5°+23.5°	G=0.0
1.00	0.87	1205	671		
2.00	1.74	301	168		
3.00	2.61	134	75		
4.00	3.49	75	42		
5.00	4.36	48	27		