

Luminaire

Code M327420
Name EVERYT 80 SQ FI LED 2700K 2X22° N/B

Measurem.

Code FTS1602752-A
Name EVERYT 80 SQ FI LED 2700K 2X22° N/B

Luminaire Flux	789 lm	Luminaire Power	10.0 W	Efficacy	78.900 lm/W	Efficiency	100.00%
Source Flux	789 lm	Maximum value	1439.60 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	80 mm	Width	80 mm	Height	115 mm
Rectangular Luminous Area		Length	60 mm	Width	60 mm	Height	0 mm
Horizontal Luminous Area		0.003600 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000871 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		20-05-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		789 lm	


LED Flux=1474lm LED Power=10W Eff=54% EfcLed=147lm/W EfcLum=79lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(9k)=50000h

C.I.E. 93 100 100 100 100
F UTE 1.00 A

D DIN 5040
B NBN

A60
BZ 1


80mm x 80mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
DLOR 100.00 %
RN 0.00 %



Luminaire

Code M327420
Name EVERYT 80 SQ FI LED 2700K 2X22° N/B

Measur. Code

Code FTS1602752-A
Name EVERYT 80 SQ FI LED 2700K 2X22° N/B

Luminaire Flux	789 lm	Luminaire Power	10.0 W	Efficacy	78.900 lm/W	Efficiency	100.00%
Source Flux	789 lm	Maximum value	1439.60 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	80 mm	Width	80 mm	Height	115 mm
Rectangular Luminous Area		Length	60 mm	Width	60 mm	Height	0 mm
Horizontal Luminous Area		0.003600 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000871 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		20-05-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		789 lm	


LED Flux=1474lm LED Power=10W Eff=54% EfcLed=147lm/W EfcLum=79lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(9k)=50000h

C.I.E.	93 100 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.44	0.88	1.31	1.75	2.19	OC	0.44	0.88	1.31	1.75	2.19
OB	0.44	0.88	1.31	1.75	2.19	OD	0.44	0.88	1.31	1.75	2.19

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1135.84	1087.62	829.27	526.97	243.46	63.83	11.23	1.33	0.63	0.29
OB	1135.84	1087.62	829.27	526.97	243.46	63.83	11.23	1.33	0.63	0.29
OC	1135.84	1087.62	829.27	526.97	243.46	63.83	11.23	1.33	0.63	0.29
OD	1135.84	1087.62	829.27	526.97	243.46	63.83	11.23	1.33	0.63	0.29



H[m]	D[m]	Max lux	Med lux	Alpha=23.6°+23.6°	G=0.0
1.00	0.88	1136	623		
2.00	1.75	284	156		
3.00	2.63	126	69		
4.00	3.50	71	39		
5.00	4.38	45	25		