

Luminaire

Code M328545_30°
Name EVERY 105 RD TR OR LED 2700K 2X14°ME/N_30°

Measurement

Code FTS2400251.
Name EVERY 105 RD TR OR LED 2700K 2X14°ME/N_30°

Luminaire Flux	953 lm	Luminaire Power	10.0 W	Efficacy	95.300 lm/W	Efficiency	100.00%
Source Flux	953 lm	Maximum value	1249.11 cd/klm	Position	C=0.00 G=19.00	CG	Sym. on planes 0-180
Round Luminaire		Diam.	85 mm	Height	130 mm		
Round Luminous Area		Diam.	80 mm	Height	0 mm		
Horizontal Luminous Area			0.005027 m ²	Emitting area on Plane 180°			0.000000 m ²
Emitting area on Plane 0°			0.000000 m ²	Emitting area on Plane 270°			0.000000 m ²
Emitting area on Plane 90°			0.000000 m ²	Glare area at 76°			0.001216 m ²
Coordinate system		CG		Symmetry Type		Sym. on planes 0-180	
Date		06-06-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		953 lm	
LED Flux=1474lm LED Power=10W Eff=65% EfcLed=147lm/W EfcLum=95lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(9k)=50000h							
C.I.E.	77 97 100 100 100			D DIN 5040	A60		
F UTE	1.00 B			B NBN	BZ 1		



