

Luminaire

Code M329345_0°
Name EVERY 105 CA TR OR LED 2700K 2X9°NO/NE_0°

Measurement

Code FTS2400265.
Name EVERY 105 CA TR OR LED 2700K 2X9°NO/NE_0°

| | | | | | | | |
|--|--------|-----------------|----------------|-----------------------------|---------------|-----------------|-----------------|
| Luminaire Flux | 793 lm | Luminaire Power | 10.0 W | Efficacy | 79.300 lm/W | Efficiency | 100.00% |
| Source Flux | 793 lm | Maximum value | 3770.96 cd/klm | Position | C=0.00 G=0.00 | CG | Rotosymmetrical |
| Rectangular Luminaire | | Length | 85 mm | Width | 85 mm | Height | 130 mm |
| Rectangular Luminous Area | | Length | 80 mm | Width | 80 mm | Height | 0 mm |
| Horizontal Luminous Area | | 0.006400 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.001548 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Rotosymmetrical | |
| Date | | 06-06-2024 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 793 lm | |
| LED Flux=1474lm LED Power=10W Eff=54% EfcLed=147lm/W EfcLum=79lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(9k)=50000h | | | | | | | |
| C.I.E. | 99 | 100 | 100 | 100 | D DIN 5040 | A60 | |
| F UTE | -- | | | | B NBN | BZ 1 | |

85mm x 85mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
DLOR 100.00 %
RN 0.00 %



