


Luminaire

Code NL1907260K002
 Name Parabola 100 Round 60° finitura grigia 3000K

Measurement

Code FTS1601867
 Name Parabola 100 Round 60° finitura grigia 3000K

Luminaire Flux	1310.17 lm	Luminaire Power	17.00 W	Efficacy	77.07 lm/W	Efficiency	100.00%
Lamps Flux	1310.17 lm	Maximum value	850.37 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area	Diam. 100 mm Diam. 75 mm	Height	100 mm	Height	100 mm 0 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°	0.004418 m2 0.000000 m2 0.000000 m2	Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°			0.000000 m2 0.000000 m2 0.001069 m2		
Coordinate system Date Measurement Distance	CG 15-12-2014 0.00	Symmetry Type Maximum Gamma Angle Measurement Flux			Rotosymmetrical 90 1310.17 lm		
LED Flux=2103lm LED Power=17W Eff=62,3% EfcLed=124lm/W EfcLum=77lm/W Ra=90 SDCM=3 L70(6K)=60000h							
C.I.E. F UTE	76 95 100 100 100 1.00 B	D DIN 5040 B NBN			A60 BZ 1		



Luminaire

Code NL1907260K002
Name Parabola 100 Round 60° finitura grigia 3000K

Measurement


Code FTS1601867
Name Parabola 100 Round 60° finitura grigia 3000K

Luminaire Flux	1310.17 lm	Luminaire Power	17.00 W	Efficacy	77.07 lm/W	Efficiency	100.00%
Lamps Flux	1310.17 lm	Maximum value	850.37 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	100 mm	Height	100 mm		
Round Luminous Area		Diam.	75 mm	Height	0 mm		
Horizontal Luminous Area	0.004418 m2			Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°	0.000000 m2			Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°	0.000000 m2			Glare area at 76°		0.001069 m2	
Coordinate system	CG			Symmetry Type		Rotosymmetrical	
Date	15-12-2014			Maximum Gamma Angle		90	
Measurement Distance	0.00			Measurement Flux		1310.17 lm	
LED Flux=2103lm LED Power=17W Eff=62,3% EfcLed=124lm/W EfcLum=77lm/W Ra=90 SDCM=3 L70(6K)=60000h							
C.I.E.	76 95 100 100 100			D DIN 5040	A60		
F UTE	1.00 B			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.58	1.17	1.75	2.34	2.92	OC	0.58	1.17	1.75	2.34	2.92
OB	0.58	1.17	1.75	2.34	2.92	OD	0.58	1.17	1.75	2.34	2.92

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1114.12	1099.61	984.53	737.69	397.49	208.39	124.01	55.18	13.39	0.59
OB	1114.12	1099.61	984.53	737.69	397.49	208.39	124.01	55.18	13.39	0.59
OC	1114.12	1099.61	984.53	737.69	397.49	208.39	124.01	55.18	13.39	0.59
OD	1114.12	1099.61	984.53	737.69	397.49	208.39	124.01	55.18	13.39	0.59



H[m]	D[m]	Max lux	Med lux	Alpha=30.3°+30.3°	G=0.0
1.00	1.17	1114	581		
2.00	2.34	279	145		
3.00	3.50	124	65		
4.00	4.67	70	36		
5.00	5.84	45	23		

Luminaire

Code NL1907260K002
 Name Parabola 100 Round 60° finitura grigia 3000K

Measurerm.

Code FTS1601867
 Name Parabola 100 Round 60° finitura grigia 3000K

Luminaire Flux	1310.17 lm	Luminaire Power	17.00 W	Efficacy	77.07 lm/W	Efficiency	100.00%
Lamps Flux	1310.17 lm	Maximum value	850.37 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

UGR
 S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
WorkingPlane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
RoomDimensions	ViewedCrosswise					ViewedEndwise				
x=2H y=2H	24.3	25.2	24.5	25.4	25.6	24.3	25.2	24.5	25.4	25.6
x=2H y=3H	24.7	25.5	25.0	25.7	26.0	24.7	25.5	25.0	25.7	26.0
x=2H y=4H	24.7	25.5	25.0	25.7	26.0	24.7	25.5	25.0	25.7	26.0
x=2H y=6H	24.7	25.4	25.0	25.7	26.0	24.7	25.4	25.0	25.7	26.0
x=2H y=8H	24.6	25.3	25.0	25.6	25.9	24.6	25.3	25.0	25.6	25.9
x=2H y=12H	24.6	25.2	24.9	25.6	25.9	24.6	25.2	24.9	25.6	25.9
x=4H y=2H	24.6	25.3	24.9	25.6	25.9	24.6	25.3	24.9	25.6	25.9
x=4H y=3H	25.0	25.7	25.4	26.0	26.3	25.0	25.7	25.4	26.0	26.3
x=4H y=4H	25.1	25.7	25.5	26.0	26.4	25.1	25.7	25.5	26.0	26.4
x=4H y=6H	25.1	25.6	25.5	25.9	26.3	25.1	25.6	25.5	25.9	26.3
x=4H y=8H	25.1	25.5	25.5	25.9	26.3	25.1	25.5	25.5	25.9	26.3
x=4H y=12H	25.0	25.4	25.5	25.8	26.2	25.0	25.4	25.5	25.8	26.2
x=8H y=4H	25.1	25.5	25.5	25.9	26.3	25.1	25.5	25.5	25.9	26.3
x=8H y=6H	25.1	25.4	25.5	25.8	26.3	25.1	25.4	25.5	25.8	26.3
x=8H y=8H	25.0	25.3	25.5	25.8	26.2	25.0	25.3	25.5	25.8	26.2
x=8H y=12H	25.0	25.2	25.5	25.7	26.2	25.0	25.2	25.5	25.7	26.2
x=12H y=4H	25.1	25.4	25.5	25.8	26.3	25.1	25.4	25.5	25.8	26.3
x=12H y=6H	25.0	25.3	25.5	25.8	26.2	25.0	25.3	25.5	25.8	26.2
x=12H y=8H	25.0	25.2	25.5	25.7	26.2	25.0	25.2	25.5	25.7	26.2